

IP CCTV / Professional IP cameras / Hikvision / Bullet Cameras

DS-2CD1T47G2H-LIU(2.8mm)

HIKVISION



Features

- Hikvision
- Value Range
- Bullet IP camera
- 1/3" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.8 mm Lens
- 0 Lux
- Hybrid light: IR and White Light
- Hybrid light range 50 m
- ColorVu: color image 24 hours
- Compression H.265+ / H.265 / H.264+ / H.264
- Motion Detection 2.0
- WDR (120 dB)
- 3D DNR
- Integrated microphone
- RJ-45 10/100M BaseT
- PoE IEEE802.3af
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- Weatherproof IP67

Specifications

Brand	HIKVISION
Range	Value
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	20 fps (2560x1440), 25 fps (1920x1080, 1280x720)
Extra Stream rate	25 fps (1280x720, 640x480, 640x360)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 115°, V: 60°, D: 143°
Range performance	64 m (D), 25 m (O), 12 m (R), 6 m (I)
Minimum illumination	Colour: 0.001 Lux @(F1.0, AGC ON) 0 Lux with IR
Supplementary lighting	Hybrid light: IR Range 50 m White light range 50 m
Day/Night	ColorVu: Color image 24 hours
Image improvements	WDR (120 dB), BLC, HLC, 3D-DNR, AGC, AWB, ROI, Mirror function, Privacy masking
Motion Detection	Motion detection 2.0 with human and vehicle classification applied in motion detection.
Internal memory	Does not have
Audio	Integrated microphone
Audio type	Mono
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/AAC-LC
Audio bitrate	64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/16 to 64 Kbps (AAC-LC)
Network interface	Ethernet 10/100M BaseT
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ONVIF (Profiles S, T), ISAPI, SDK

Power	DC 12 V / 570 mA / 6.8 W max. PoE IEEE802.3af
Degree of protection	Weatherproof IP67
Material	Front cover: Metallic Body: Plastic Bracket: Plastic
Temp. operation	-30° C ~ +60° C
Dimensions	81 mm (H) x 83.7 mm (W) x 201.96 mm (D)
Base dimensions	Ø base 70.08 mm / Ø entre tornillos 55 mm / 3 tornillos
Weight	550 g