

KIT-PEOPLECOUNT-1PRO

Multi-Stance Capacity Control Kit
Camera IPCOUNT-3D-EXT-0280
PC with SF-COUNT-MULTIROOM
software
Multiple viewers at the entrances
Customized reports
Multi-channel system up to 100
cameras



Full Capacity Control Kit in 1 Multi-Stance
People counting camera IPCOUNT-3D-EXT-0280
PC with installed SF-COUNT-PRO software
Capacity control up to 20 rooms
Multi-channel system up to 100 people counting cameras (Expandable)
Capacity per camera, floor, room or in total
Hourly, daily, monthly and yearly statistical reports
Multiple viewers on different devices via web server
Sound and visual notification on the screen when the permitted capacity is reached
Fully centralized

Specifications

IP camera

Model	IPCOUNT-3D-EXT-0280
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	3 Mpx
Main Stream rate	2048 x 1536
Compression	H.265+ / H265 / H.264+ / H.264
Day / Night	Auto / Programmable / Manual
Infrared Illumination	20 m
Bitrate	3 Kbps ~ 16 Mbps
Lens	2.8 mm (H: 96°, V: 70°)
Functions	3D-DNR, BLC, DWDR
Communication interface	1 x Ethernet 10/100M BaseT
Alarms	2 input / 2 output (Supports up to 30 VDC, 1 A / 50 VDC, 0.5 A)
Audio	2 IN / 1 OUT
People counting	Statistics of entries, exits and transit Daily, weekly, monthly and annual reports
Other functions	Height Filter Door Status Indicator
Remote access	Web Browser, Smartphone App and Capacity Control Software
Interoperability	ONVIF
Power	DC 12 V / 600 mA, PoE (IEEE802.3af)
Temp. operation	-40° C ~ +60° C
Degree of protection	Interior
Material	Body: Metallic
Dimensions	61.5 (H) x 204 (W) x 78 (D) mm
Base dimensions	42 x 65 mm / 4 screws
Weight	810 g
Software	
Model	SF-COUNT-PRO (Safire Doors Pro)
Capacity Control	Control over 20 occupancies
Cameras	Up to 100 people counting cameras (Supports Safire, Uniview and X-Security devices)
Display	Via web browser. Unlimited devices and independent image on each device.
Reports	Personalized. Ability to download reports in Excel file
Other	Customizable notifications and logos. 3 user levels: Administrator, Supervisor and Operator. Remote Update.
PC	
CPU	6-core
Memory	4GB LPDDR4
Communication	1xGigabit Ethernet, Wifi 5 (802.11ac dual band), Bluetooth 5.0, USB 3.0, USB 2.0, USB 3.0 (Type C)

Audio	MIC Input / 3.5mm Jack & HDMI Output
Video	1 x HDMI 2.0 (Type A) Up to 4K @ 60 FPS
Operating System	Linux Based
Power	DC 5V / 3A