# **NVS-VIDEOINTERCOM-2W-KPAD**

#### **NIVIAN**



### **Features**

- Nivian
- WiFi Video Door Station Kit of 2 wires
- CMOS image sensor 1080P
- IR Range 5 m
- White LED for color night vision
- Customizable call button
- Keypad for fixed or single-use PIN code accesses

- Two-way audio (integrated mic and speaker)
- Mifare card reader
- 2 outputs for electric locks (1 E-lock powered output and 1 relay output)
- Touch monitor 7"
- WiFi 2.4 GHz
- Micro SD card slot up to 128 GB
- Tuya Smart App

## **Specifications**

### **PLACA-2W-KPAD**

| Brand                    | Nivian   |
|--------------------------|--|
| System                   | Linux  |
| Camera                   | 2 MP CMOS  |
| Resolution               | 1080P  |
| Lens                     | Viewing angle 110º (diagonal)  |
| Audio                    | Bidirectional with microphone and speaker with noise reduction   |
| Keypad                   | Access with fixed or single-use PIN code   |
| Communication            | 2 Technology - wires (the plate does not need a power supply) The maximum distance from the monitor to the plate is 100 m Recommended cable diameter (0.75mm)          |
| Power                    | Powered from indoor monitor  |
| Door opening             | 2 electric lock relay outputs:<br>1 relay (de-energized) for already powered locks (existing)<br>1 live relay for powering a new lock without a power<br>supply nearby |
| Environmental protection | Exterior (waterproof IP65))  |
| Working temperature      | -40°C ~ +55°C  |
| Dimensions               | 168 x 88 x 34 mm   |
| Weight                   | 340 g  |
|                          |  |

### MONITOR-2W-KPAD

| Brand                           | Nivian   |
|---------------------------------|--|
| Operating System                | Linux  |
| Screen                          | 7" TFT Touch LCD   |
| Resolution                      | 1024 X 600   |
| Audio                           | Two-way audio with microphone and speaker with noise reduction |
| Connection to the outdoor panel | 2-hilos wired technology (the board does not need power cable) |

| Internet connection | WiFi 2.4Ghz   |
|---------------------|---|
| Remote management   | Tuya Smart App - Call notification and remote opening |
| CCTV Management     | Supports up to 8 IP cameras using ONVIF support       |
| Image recording     | MicroSD card up to 128 GB (Not included)              |
| Power               | 24V/2ADC Power supply - Consumption 9.5W / Rest 5W    |
| Working temperature | -10°C ~ +55°C   |
| Material            | Aluminum, Methacrylate and ABS Plastic                |
| Dimensions          | 192 x 128 x 17.6 mm                                   |
| Weight              | 342 g   |
|                     |   |