

Video-intercoms / Nivian / Kits

NVS-VIDEOINTERCOM-WIRELESS

NIVIAN



Features

- Nivian
- HaLow WiFi Wireless Video Door Station Kit (up to 500m))
- CMOS image sensor 1080P
- IR Range 5 m
- White LED for color night vision
- Customizable call button
- Two-way audio (integrated mic and speaker)
- Dual WiFi 2.4 GHz / 5 GHz
- 1 E-lock powered output and 1 relay output)
- Touch monitor 7"
- Micro SD card slot up to 128 GB
- Tuya Smart App

Specifications

MONITOR-WIRELESS

Brand	Nivian
Range	Smart Security
Operating System	Linux
Screen	7" TFT Touch LCD
Resolution	1024 X 600
Audio	Two-way audio with microphone and speaker with noise reduction
Connection to the outdoor panel	Wireless via long-range HaLow technology (500 m in open space)
Compatibility with CCTV cameras	Not applicable
Internet connection	Dual WiFi 2.4 / 5 GHz
Remote management	Tuya Smart App - Call notification, remote opening and intelligent automations
Image recording	MicroSD card up to 128 GB (Not included)
Additional connections	1 Input for buzzer
Power	DC power supply 12V (included) - Consumption 9.5W / Rest 5W
Working temperature	-10°C ~ +55°C
Environmental protection	Valid for interior
Material	Methacrylate and ABS Plastic
Dimensions	190 x 127 x 20 mm
Weight	354 g

WIRELESS-PLATE

Brand	Nivian
System	Linux
Camera	Image sensor 1/3" CMOS
Resolution	1080P

Lens	Viewing angle 110° (diagonal)
IR night vision	Automatic white LED
Audio	Two-way audio with microphone and speaker with noise reduction
Communication	Wireless via long-range HaLow technology (500 m in open space)
Power	Supports DC 9~24 V - DC power supply 12 V (included) - Optional solar operation with NV-KITSOLAR-VINTERCOM-WIRELESS
Door opening and connections	1 Relay output NO without voltage (The lock must be powered from the outdoor panel power supply) - 1 Input for output push button
Opening options	From monitor, mobile app
Environmental protection	Outdoor / Waterproof IP65 / Tamper alarm
Material	Special technical ABS plastic for transmission of long-range wireless waves
Working temperature	'-40°C ~ +55°C
Dimensions	180 x 65 x 44 mm
Weight (without packaging)	120 g