

IP CCTV / Professional IP cameras / Safire / Bullet Cameras

SF-IPB779Z-4Y-AI-25x

SAFIRE



Features

- Safire
- IP Bullet Camera
- Projects Range
- 1/2.5" Progressive Scan CMOS
- 4 Megapixel (2560x1440) @ 60FPS
- 4.7~118 mm motorised varifocal autofocus lens
- Image Stabilization (EIS)
- Cold / snowy weather heater
- Colour: 0.009 Lux
- IR Range 200 m
- Compression H.265+/H.265/H.264+/H.264
- RJ-45 10/100/1000 Mbps BaseT
- RS-485
- Audio
- Built-in microphone
- Alarms
- PoE+ IEEE802.3at
- Waterproof IP67- Impact resistance IK10
- IR Cut
- WDR (140dB)



- 3D DNR

- SD card recording

- WEB, CMS, Smartphone and NVR interface

- ONVIF Compatible

Specifications

Brand	SAFIRE
Image sensor	1/2.5" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Image Stabilization (EIS)	Integrated gyroscope for improved performance
Main Stream rate	25fps (2688 × 1520, 2560 × 1440, 1920 × 1080, 1280 × 720) 60fps (2560 × 1440, 1920 × 1080, 1280 × 720)
Extra Stream rate	25fps (704 × 576, 640 × 480)
Third Stream Rate	25fps (1920 × 1080, 1280 × 720, 704 × 576, 640 × 480)
Fourth Stream Rate	25fps (704 × 576, 640 × 480)
Fifth Stream Rate	25fps (704 × 576, 640 × 480)
Compression	H.265+ / H265 /H.264+ / H264 / MJPEG
Bitrate	32 Kbps ~ 16 Mbps
Lens	Motorized 4.7~118 mm Autofocus (25x)
Minimum illumination	Colour: 0.009 Lux / IR LED's (200m)
Image improvements	WDR (140 dB), BLC, 3D-NR, AWB, Privacy Masking, ROI, Hall Mode
Day / Night	Removable mechanical ICR filter
Smart Features	Line Crossing, Area Intrusion, Region Entry Detection, Line Crossing Detection, Intrusion Detection, Region Entry, Region Exit (support activation of alarms by specific target types (persons and vehicles)) Scene change detection, audio exception detection, out of focus detection
Built-in heater	Built-in heater to ensure a clear picture in snowy weather
Internal memory	MicroSD card, Max 128 GB
Video output	1 composite video output (BNC connector)
Alarms	1 input / 1 relay
Audio	1 input (line in / microphone), 1 output
Communication Interface	Ethernet 10/100M BaseT 1 RS485
Remote access	Web browser, Safire Control Center Smartphone App and PC Software

Interoperability	ONVIF, PSIA, CGI
Power	DC 12 V / 1 A, PoE IEEE802.3at / 0.3A
Degree of protection	Waterproof IP67, Impact resistance IK10 TVS 4000V
Temp. operation	-40° C ~ +60° C
Dimensions	425 (D) x 190 (W) x 180 (H) mm
Weight	2160 g