

Networking / Routers / Routers 3G/4G/5G

TK-RUT360

TELTONIKA



Features

- Industrial 4G Router
- 4G Cat6 / 3G
- 1 SIM Slot
- 2 Ethernet ports RJ45 Fast Ethernet
- Wi-Fi 802.11b/g/n 2.4GHz
- Up to 2 Inputs and 2 Digital Outputs
- 2x SMA for LTE antennas and 2x RP-SMA for Wi-Fi antenna
- Industrial 4 pin DC power connector
- DC power 9 to 30V Power Supply Included
- Status LEDs

Specifications

Brand	Teltonika
Device	Industrial 4G Router
Ethernet	2 Ethernet ports RJ45 10/100Mbps (1 WAN + 1 LAN)
CPU	QCA9531, MIPS 24kc, 650 MHz
RAM	128MB DDR2
Flash	16MB
Wi-Fi features	802.11b/g/n 2.4GHz (AP Mode and STA Mode)
Type of 4G	Cat 6 to 300Mbps
Operating System	RutOS (Based on OpenWRT)
Network Protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DHCP, DNS, HTTP, HTTPS, SSL v3, TLS, ARP, PPPoE, UPNP, SSH, Telnet, SNMP
VPN Protocols	OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP
Monitoring and Management	WEB UI, SSH, SMS, SNMP, JSON-RPC, FOTA, RMS
Cloud Solutions	RMS, FOTA, Telenor, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx
Inputs and Outputs	2 x Digital Inputs and Outputs. Digital Input to 0 - 5 V detected as low level, 8 - 30 V detected as high level. Open collector, maximum output 30 V, 300 mA
Services	DDNS, VRRP, Wake On Lan (WOL), WEB filter, UPNP, Traffic Logging
Power	DC connector 4 Industrial pins 9~30V Power Supply Included
Material	Aluminium
Temp. operation	-40° C ~ +75° C
Operating humidity	10 ~ 90 % (non-condensing)
Optional Mounting Kit (Not included)	Rail Mounting Kit, Compact Rail Mounting Kit, Surface Mounting Kit
Dimensions	30 (Al) x 100 (W) x 85 (D) mm
Weight	247 g
Region	Europe, Middle East, Africa, Australia, APAC2, Brazil, and Malaysia