

Video-intercoms / Uniview / Kits

UV-KIT/201S/372S/NSW2020

Uniview



Features

- Uniview
- Video intercom kit
- Tecnología IP & WiFi
- Kit consisting of: UV-OEU-201S-HMK-W outdoor surface video door entry panel with 2 Mpx HD camera, UV-OEI-372S-H-W indoor WiFi monitor with 7" TFT LCD screen and UV-NSW2020-6T-POE-IN PoE switch
- MF Card Reader
- Monitoring via UNV-Link mobile app

Specifications

UV-OEI-372S-H-W

Brand	Uniview
Model	OEI-372S-H-W
Operating system	Linux
Screen type	7" color touch-screen TFT
Screen resolution	1024 x 600
Inputs	8 x configurable alarm inputs, 1 x RS485
Outputs	2 x relay outputs
Audio	Two-way audio with integrated microphone and loudspeaker Noise reduction and echo cancellation
Equipment capacity	Up to 20 total equipment (boards and monitors)
Memory	MicroSD card slot (up to 32 GB)
Connection	Ethernet 10/100 BaseT / WiFi 802.11 b/g/n (only supports 2.4 GHz)
Remote access	Web browser UNV-Link mobile app
Power	DC 12 V / 1 A max. / IEEE802.3af PoE
Temp. operation	-10 °C ~ +55 °C
Dimensions	143 (H) x 193 (W) x 25 (D) mm
Weight	360 g

UV-OEU-201S-HMK-W

Brand	Uniview
Model	OEU-201S-HMK-W
Operating system	Linux
Image sensor	2 Mpx CMOS wide-angle IR
Image Functions	BLC / WDR / DNR

Viewing angle	H: 124°, V: 68°, V: 147°
Audio	Bidirectional audio with microphone and speaker
Access control	Door opening with MF card 13.56 MHz Up to 2.000 users and 10.000 cards
Keypad	Mechanical call button
Outputs	2 x relay for lock, 1 x RS485
Inputs	4 x auxiliary inputs (output button, feedback, door sensor), 1 x tamper
Storage	MicroSD card (only used for debug, not for storage)
Equipment capacity	Up to 20 total equipment (boards and monitors)
Remote access	Web browser UNV-Link mobile application
Network interface	Ethernet 10/100 BaseT / WiFi (only supports 2.4 GHz)
Power	DC 12 V / 1000 mA máx. / IEEE802.3af PoE
Degree of protection	Suitable for exterior IP65 Anti-vandal IK08
Material	Aluminium alloy
Temp. operation	-30 °C ~ +60 °C
Dimensions	171 (H) x 79 (W) x 34 (D) mm
Weight	270 g

UV-NSW2020-6T-POE-IN

Brand	Uniview
Device	Unmanaged PoE Switch
Interface	6 Ports RJ45 10/100Mbps
IEEE standards compliance 802.3	802.3i, 802.3u, 802.3ab, 802.3x, 802.3az
PoE characteristics	4 802.3af/at PoE+ Ports Up to 30W per port Total PoE power of 60W
Functions	VLAN mode Default mode Extended Mode
Packet Buffer	448k
Bandwidth	1,2Gbps

Packet Forwarding Rate	0,90Mbps
MAC Table	1K
Supported Technologies	Auto-Negotiation / Auto MDI/MDIX mode
Power	48/51V DC, adapter-powered (AC100-240V, 50/60Hz)
Maximum Consumption	< 60W
Operating temperature	0° C ~ 40° C
Dimensions	107 x 101 x 25 mm
Weight	0,19 Kg