

# UV-OEU-201B-HMK-W

Uniview



## Features

---

- Uniview
- IP video door entry system with 2 Mpx camera for 1 apartment
- Wide angle lens
- Built-in speaker and microphone
- IR night vision
- Conexión TCP/IP, WiFi y RS485
- PoE IEEE802.3af
- MF Card Reader
- Remote monitoring via UNV-Link mobile app or indoor monitor
- Remote door opening
- Surface mounting
- Plastic housing
- Suitable for exterior IP65
- Anti-vandal IK08

## Specifications

|                      |                                                                           |
|----------------------|---------------------------------------------------------------------------|
| Brand                | Uniview                                                                   |
| Model                | OEU-201B-HMK-W                                                            |
| Operating system     | Linux                                                                     |
| Image sensor         | 2 Mpx CMOS wide-angle IR                                                  |
| Image Functions      | BLC / WDR / DNR                                                           |
| Viewing angle        | H: 124°, V: 68°, V: 147°                                                  |
| Audio                | Bidirectional audio with microphone and speaker                           |
| Access control       | Door opening with MF card 13.56 MHz<br>Up to 2.000 users and 10.000 cards |
| Keypad               | Mechanical call button                                                    |
| Outputs              | 2 x relay for lock, 1 x RS485                                             |
| Inputs               | 4 x auxiliary inputs (output button, feedback, door sensor), 1 x tamper   |
| Equipment capacity   | Up to 20 total equipment (boards and monitors)                            |
| Remote access        | Web browser<br>UNV-Link mobile application                                |
| Network interface    | Ethernet 10/100 BaseT / WiFi                                              |
| Power                | DC 12 V / 1000 mA máx. / IEEE802.3af PoE                                  |
| Degree of protection | Suitable for exterior IP65<br>Anti-vandal IK08                            |
| Material             | Plastic                                                                   |
| Temp. operation      | -30° C ~ +60° C                                                           |
| Dimensions           | 171 (H) x 79 (W) x 34 (D) mm                                              |
| Weight               | 260 g                                                                     |