

# UV-UHO-P2S-M33F34

Uniarch



## Features

---

- Uniarch
- Panda P Series
- PT WIFI IP Camera
- **Double lens:** Integration of a fixed lens camera for general situation observation and a PT camera for tracking or focusing on other off-scene details
- Lente panorámica de 2.8 mm con sensor de 1/2.8" y resolución 3MP (2304\*1296)@25/20fps
- Lente PT de 4mm con sensor de 1/2.8" y resolución 3MP (2304\*1296)@25/20fps
- Ultra 265, H.265, H.264
- Supports digital WDR
- Built-in microphone and speaker, supports two-way audio, provides better interaction
- Supports deterrent sound and light, makes deterrence more noticeable in case of alarm
- Supports automatic tracking (Autotracking)
- Human and vehicle detection
- IR night vision, up to 30 m IR distance
- White light, up to 30 m white light distance
- Supports dual light mode: Changes between infrared and white light automatically when preset is activated.
- Supports 512 Micro SD card of [%VAR%] GB
- Wi-Fi connection and easy installation
- Suitable for exterior IP66

## Specifications

---

<b>Brand</b>	Uniarch
<b>Image sensor</b>	1/2.8" Progressive Scan CMOS
<b>Maximum resolution</b>	3 Megapixel (2304x1296)
<b>Fixed lens</b>	2.8 mm
<b>PT Lens</b>	4.0 mm
<b>Main Stream rate</b>	Panoramic / PT: 3MP (2304x1296)@15fps; 2MP (1920x1080)@15fps; 720P (1280x720)@15fps
<b>Extra Stream rate</b>	Panoramic / PT: 640x360@15fps; 2CIF (704x288)@15fps; CIF (352x288)@15fps
<b>Video compression</b>	Ultra 265, H.265, H.264, MJPEG
<b>Minimum illumination</b>	Colour: 0.003 lux (F1.6 AGC ON) 0 lux with IR on
<b>Infrared range</b>	Overview: 30 m PT: 30 m
<b>Detection functions</b>	Motion Detection, Ultra Motion Detection, Audio Detection, Tamper Alarm.
<b>Image improvements</b>	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
<b>Day / Night</b>	Mechanical ICR filter
<b>Internal memory</b>	MicroSD card, Max 512 GB
<b>Alarms</b>	Does not have
<b>Audio</b>	Built-in microphone and speaker
<b>Audio Compression</b>	G.711U, G.711A
<b>Wi-Fi</b>	IEEE802.11b/g/n/ax
<b>WI-FI frequency range</b>	2.4 GHz ~ 2.4835 GHz
<b>Autotracking</b>	Support
<b>Remote access</b>	Web Browser, CMS Software (EZStation), Smartphone (UNV-LINK, UNV-LINK Pro, Uniarch APP)
<b>Power</b>	DC 12V / 10W
<b>Temp. operation</b>	-30° C ~ 60° C
<b>Degree of protection</b>	Waterproof IP66, overvoltage 4KV

**Dimensions**

Ø117(W) x 117(D) x 202(H) mm

---

**Weight**

610 g

---