

Analogue CCTV / HD 4n1 / XVRs / Uniview / Uniarch

UV-XVR301-04Q

Uniview



Features

- Uniview
- DVR 5n1
- Easy range
- 4 BNC video CH (IP-replaceable)
- AHD, TVI, CVI, CVBS, CVBS
- 48 Mbps bandwidth supported
- Maximum IP resolution 4K
- Maximum analog resolution 8 Mpx
- Audio
- HDMI and VGA output
- 2 x USB 2.0
- Mouse
- Space for 1 HDD up to 8 TB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniview
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4CH BNC
Hybrid configuration	Up to 6 IP Channels (4K) replacing all the BNC channels
Video outputs	1 HDMI, 1 VGA
Audio inputs	1 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Maximum IP recording resolution	4 Mpx
Analog recording resolution	AHD: 8MP@15FPS (first channel); 5MP@20fps; 4MP@30fps; 4MP@30fps; 3MP@30fps(primer channel); 1080P@30fps; 720P@60fps TVI: 8MP@15FPS (first channel); 5MP@20fps; 4MP@30fps; 4MP@30fps; 3MP@20fps(primer channel); 1080P@30fps; 720P@60fps CVI:8MP@15fps(primer channel); 5MP@20fps; 4MP@30fps; 1080P@30fps; 720P@30fps Supports CVBS *For the correct live display, the combination of resolution and FPS of the connected analog cameras must be equal to or lower than the specifications indicated, but in no case higher than the specifications indicated.
Main Stream recording encoding	8MP Lite@8fps (first channel); 5MP Lite@12fps; 4MP Lite@15fps; 3MP Lite@15fps(primer channel); 1080P@15fps; 720P@30fps
Extra Stream recording encoding	D1@12FPS(máx)
Recording method	Manual, programmed, motion detection
Internal memory	1 HDD SATA 3.5" of up to 8TB (not included)
External interface	2 x USB (Mouse and backup) / RJ45 10M/100M/1000M (Ethernet)
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 12V / 8W
Dimensions / Weight	46 (H) x 260 (W) x 240 (D) mm / 1.1 kg