

IP CCTV / IP solutions / Retail

# XS-IPD360A-5U-AI

## X-SECURITY



## Features

---

- X-Security
- IP Fisheye Camera
- ULTRA Range
- 1/2.7" Progressive CMOS
- 5 Megapixel (2592 × 1944)
- 1.4 mm Lens
- 0.006 Lux
- IR 10m
- Compression H.265+/H.265/H.264+/H.264
- RJ-45 10/100 BaseT
- PoE IEEE802.3af
- IVS
- Intelligent search
- People count
- Heat map
- Built-in microphone
- WDR 120dB
- SD card recording
- WEB Interface, CMS (DSS/ PSS), Smartphone and NVR
- ONVIF Compatible



• Weatherproof IP67

## Specifications

|                            |                                                                                                                                       |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Brand                      | X-SECURITY                                                                                                                            |
| Image sensor               | 1/2.7" Progressive CMOS                                                                                                               |
| Maximum resolution         | 5 Megapixel (2592 × 1944)                                                                                                             |
| Lens                       | 1.4 mm (H: 180°; V: 180°; D: 180°)                                                                                                    |
| Main Stream rate           | (2592×1944 @1–25/30 fps)                                                                                                              |
| Extra Stream rate          | (704×576 @1–25 fps/704×480 @1–30 fps)                                                                                                 |
| Compression                | H.265; H.264; H.264H; H.264B; MJPEG (only compatible with substream)                                                                  |
| Infrared lighting          | 0.006 Lux@F2.0 (color, 30IRE)<br>0,0006 Lux@F2,0 (N/N, 30IRE)<br>0 Lux (illuminator on)                                               |
| Range performance          | 28 (D), 11.2 (O), 5.6 (R), 2.8 (I)                                                                                                    |
| Image improvements         | WDR 12dB, BLC, HLC, AWB, AGC, 3D-DNR,                                                                                                 |
| IVS (Perimeter protection) | Tripwire; intrusion                                                                                                                   |
| People count               | Count of people in the area, display and issue annual / monthly / daily reports (matching devices needed); Count of people in 4 areas |
| Intelligent search         | Work in conjunction with Smart NVR to perform intelligent searches, event extraction and merging with event videos.                   |
| Heat map                   | Yes                                                                                                                                   |
| Network interface          | Ethernet 10/100 BaseT                                                                                                                 |
| Audio                      | Integrated microphone                                                                                                                 |
| Audio Compression          | PCM; G.711a; G.711Mu; G726                                                                                                            |
| Audio inputs               | 1/1                                                                                                                                   |
| Alarms                     | 1 input channel: 5mA 3V–5V DC<br>1 output channel: 300mA 12V DC                                                                       |
| Remote access              | WEB, CMS (DSS/PSS), Smartphone and NVR interface                                                                                      |
| Interoperability           | ONVIF (Profile S/Profile G/Profile T); .CGI; Hito; Genetec; P2P                                                                       |
| Material                   | Metal + plastic                                                                                                                       |
| Power                      | DC 12 V / 4,4W, PoE IEEE802.3af                                                                                                       |
| Temp. operation            | -40° C ~ +60° C                                                                                                                       |

|                      |                        |
|----------------------|------------------------|
| Internal memory      | Micro SD Max 256GB     |
| Degree of protection | Weatherproof IP67      |
| Dimensions           | 44,6 mm(H) × 126,2? mm |
| Weight               | 299 g                  |