

XS-IPD844ZSWHA-4U

X-Security IP Dome Camera

4 Megapixel (2688x1520)

2.7 ~ 13.5 mm varifocal lens

Motorised Autofocus

PoE | IEEE802.3af | H.265+ Audio |

Alarm

Weatherproof IP67 Anti-vandal IK10



X-Security

IP camera

ULTRA Range

1/3" Progressive CMOS

4 Megapixel (2688x1520)

2.7~13.5 mm motorised varifocal autofocus lens

High sensitivity Starlight

0.005 Lux

IR Array Range 40 m

Compression H.265+/H.265/H.264+/H.264

RJ-45 10/100 BaseT

PoE IEEE802.3af

Weatherproof IP67

Vandal proof IK10

Recognition of humans and vehicles

Intelligent motion detection

WDR

IR Cut

Audio

Alarms

WEB Interface, CMS (DSS/ PSS), Smartphone and NVR

ONVIF Compatible

Specifications

Brand	X-SECURITY
Image sensor	1/3" Progressive CMOS
Maximum resolution	4 Megapixel (2688x1520)
Main Stream rate	2688x1520 (1~25/30 FPS)
Extra Stream rate	2 ^o : 704x576 (1~25 FPS), 704x480 (1~30 FPS); 3 ^o : 1280x520 (1~25/30 FPS)
Compression	H.265+/H.265/H.264+/H.264
Lens	2.7 ~ 13.5 mm (H: 104°-27°)(V:55°-15°)
Minimum illumination	0.005 Lux (Colour)
Infrared lighting	0 Lux / IR LEDs (40 m)
Image improvements	WDR, BLC, HLC, AWB, AGC, 3D-NR, ROI , Smart IR
Day / Night	Removable mechanical ICR filter
Network interface	Ethernet 10/100 BaseT
Alarm	IN / OUT
Audio	IN / OUT
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Power	DC 12 V / 708 mA, PoE IEEE802.3af
Temp. operation	-30° C ~ +60° C
Degree of protection	Weatherproof IP67, Anti-vandal IK10
Dimensions	89 mm (D) x 122 (Ø) mm
Weight	492 g