

XS-NVR2104-4K4PH

X-Security NVR for IP cameras
4 CH IP and 4 PoE ports
Maximum recording resolution 8 Mpx
Compression H.265 / H.264
Outputs 4K HDMI & VGA
Supports 1 hard disk



X-Security
NVR for IP cameras
4 CH
80 Mbps bandwidth supported
Maximum resolution 8 Megapixel
Compression H.265 / H.264
VGA and HDMI 4K output
IP Dual Stream Access
Mouse
Space for 1 HDD
4 PoE ports IEEE802.3af/at
WEB, CMS (DSS/PSS), Smartphone and NVR interface
ONVIF Compatible

Specifications

Brand	X-SECURITY
Inputs for IP cameras	LAN port up to 4 channels
PoE	Switch of 4 PoE channels IEEE802.3af/at
IP compatible cameras	X-SECURITY (proprietary protocol), HIKVISION, SAFIRE, ONVIF
Video outputs	1 HDMI 4K, 1 VGA
Bidirectional audio	1 input, 1 output, RCA
Video compression format	H.265 / H.264
Display resolution	3840x 2160, 1920x 1080, 1280x 1024, 1280x 720, 1024x 768
Total bandwidth	80 Mbps
Recording resolution	8Mp, 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 720P, D1...
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	No
Recording method	Manual, programmed, motion detection
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network / SATA internal interface
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2x USB 2.0 (Mouse and backup) / 1 RJ45 10/100M (Ethernet)
Remote access	Browser (ActiveX), mobile app or softwarePSS
Power	DC 48 V / 1.25 A
Dimensions	1U, 48 (H) x 260 (W) x 225 (D) mm / 0.8 Kg (without HDD)