

Analogue CCTV / HD 4in1 / Cameras / Turret cameras

XS-T887A-2E-DL

X-SECURITY



Features

- X-Security
- Turret HDTVI, HDCVI, AHD and Analog Camera
- EASY Range
- CMOS sensor
- Resolution 2 MP (1920x1080)
- Output 4in1
- 2.8 mm Lens
- 0 Lux
- Dual Light: IR and White Light
- Dual Light range 40 m
- IR Cut
- DWDR
- 3D-DNR
- Integrated microphone
- Coaxial audio in HDCVI technology
- Weatherproof IP67
- PoC, power supply through coaxial cable

Specifications

Brand	X-Security
Range	EASY
Image sensor	2 MPx Progressive CMOS
Maximum resolution	2 Mpx (1920x1080)
Resolution	TVI: 1080p (25~30 fps) CVI: 1080p (25~30 fps) AHD: 1080p (25~30 fps) CVBS: PAL/NTSC
Lens	2.8 mm
Viewing Angle (FOV)	H: 102°, V: 60°, D: 129°
Range performance	41.1 m (D), 16.5 m (O), 8.3 m (R), 4.1 m (I)
Lens Adjustment	3-axis
Minimum illumination	0.01 Lux @(F2.0, AGC ON) 0 lux with dual light
Supplementary lighting	Dual Light (IR + white light) range 40 m
Day / Night	Mechanical ICR filter
Electronic Shutter	1/25~1/100000 s
Video output	1 x BNC switchable between HDTVI / HDCVI / AHD / CVBS
Video output switching	By switch
Basic functions	OSD Menu
Image improvements	DWDR, 3D-DNR, Smart Light, BLC, HLC, AWB, AGC, Privacy Masking, Mirror Effect
Audio	Integrated microphone Audio over coaxial cable in CVI technology
Power	DC 12 V / 4.1 W max.
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-40° C ~ +60° C
Dimensions	Ø 106 mm x 99.2 mm (H)
Base dimensions	Ø base 106 mm / Ø between bolts 69 mm / 4 bolts

Weight

450 g
