

XS-V3211E

Video intercom IP
2Mpx wide angle camera
Two-way audio | Double button
Mobile App for remote monitoring
Stainless steel, vandal proof
Surface mounting



X-Security
IP video-intercom with 2Mpx camera
Wide angle lens
Integrated speaker and microphone
IR night vision
MF Card Reader 13.56MHz
TCP/IP Connection
Remote monitoring via Smart PSS software, Mobile App or interior monitor
Remote door opening
Surface mounting
Double call button
Can be powered by PoE
Vandal-proof stainless steel finish
Suitable for outdoors IP65 and anti-vandalism

Specifications

Brand	X-Security
Operating system	LINUX OS
Image sensor	1/2.8" 2 Megapixel CMOS
Lens	1.9 mm
Viewing angle	H: 140°
Audio	Bidirectional audio with microphone and speaker
Keypad	2 Mechanical call button with customized LED label
Relay	1 for lock control. Second door opening (with add-on)
Inputs	Output button and power loop.
Remote access	Web browser, Mobile App or SmartPSS software
Network interface	Ethernet 10/100 BaseT
Power	DC 12 V / 600 mA max. / (802.3af) PoE
Degree of protection	IP65, IK08
Material	Aluminium
Temp. operation	-40° C ~ +60° C
Dimensions	182 (H) x 30 (W) x 101 (D) mm
Weight	800 g