

FTL135.1 H&S

The ingredients listed in this data sheet are contained in the product identified. Exact formulations are considered proprietary and confidential and as such precise product information will not be disclosed, other than to a health professional in accordance with the regulations, without and approved Secrecy Agreement.

The company shall in no event be responsible for any damages of whatever nature directly or indirectly resulting from the publication or use of or reliance upon the data provided herein. No express or implied warranty of any kind, including warranties of sale of fitness for use.

PRODUCT IDENTIFICATION: FTL135.1

APPLICATION: INDUSTRIAL BRAKES AND CLUTCHES

1.- SPECIFICATIONS

Manufacturer:	Friction Technology LTD
Address:	Friction Technology Ltd Unit 11, (Zone 5), Cibyn. Industrial Estate. Caernarfon. Gwynedd. LL55 WALES
Telephone:	+44(0) 1286 875 197

2.- HAZARDS IDENTIFICATION

CLASSIFICATION AND IDENTIFICATION OF HAZARDS	
Hazards for the humans:	Exposure to dust created by handling of this product should be kept as low as reasonably practicable limits. Handling of product may cause skin irritation.
Hazards for the environment:	NK

3.- COMPOSITION INFORMATION

Name	CAS N°	Concentration	OEL	Exposure Limit
Barium Sulphate:	7727-43-7	5-7	Total Inhalable 10mg/m ³ Respirable 4mg/m ³	8 hour TWA
Calcium Carbonate:	1317-65-3	<1	Total Inhalable 10mg/m ³ Respirable 4mg/m ³	8 hour TWA
Graphite:	7782-42-5	12-14	Total Inhalable 10mg/m ³ Respirable 4mg/m ³	8 hour TWA

4.- EMERGENCY AND FIRST AID PROCEDURES

Inhalation:	Avoid breathing dust, if happens move to fresh air. Get medical attention in case of persistent cough
Ingestion:	If dust is swallowed, rinse mouth with water and obtain medical advice
Skin contact:	Wash with soap and water for 15 minutes. Obtain medical advice if irritation
Eye contact:	Irrigate with large amounts of water for at least 15 minutes. Obtain medical advice if irritation does not disappear

5.- FIRE HAZARD DATA

Extinguisher:	Any standard extinguishing equipment may be used
Exposure hazards:	Heated to very high temperatures, may give off toxic smokes.
Protective equipment:	Wear self-contained breathing equipment

6.- ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid breathing and inhalation of dust. Use PPE as identified in Section 8
Cleaning measures:	Dust has to be collected by cleaned with a wet cloth or vacuum
Environmental Precautions:	No special precaution required

7.- HANDLING AND STORAGE

Precautions for safe handling:	Provide appropriate exhaust ventilation at places where dust is formed.
Storage:	Liable to corrode, store in a dry place

8.- EXPOSURE CONTROLS/ PERSONAL PROTECTION

Information about design of technical facilities:	Ensure ventilation to maintain airborne dust levels to below established exposure standard. Use vacuum to remove dust instead of compressed air
Respiratory Protection:	Wear respiratory equipment if exposure limits are exceeded
Skin protection:	Handle with gloves and wear suitable protective clothing, e.g. general overalls
Eye protection:	Use appropriate goggles when machining or abrading products

9.- PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Black solid
Odour:	Characteristic Friction Material Odour
Flammability:	Will burn at elevated temperatures and when finely divided
Auto Flammability:	>350°C
Melting Point:	NA
Water Solubility:	NA
Explosive Properties:	Non-hazardous as supplied but dust from grinding can presents an explosion hazard.
Relative Density	3.30 to 3.5 g/cm ³

10.- STABILITY AND REACTIVITY

Stability:	Stable
Hazardous decomposition products:	CO, CO ₂ , phenol and formaldehyde
Incompatibility with materials:	NA
Conditions to avoid:	Prolonged exposure to elevated temperatures, >300°C
Hazardous Reactions:	Reacts with acids and H ₂ gas

11.- TOXICOLOGICAL INFORMATION

Inhalation:	May cause irritation to upper respiratory tract.
Eye contact:	May cause irritation
Skin contact:	May cause irritation
Ingestion:	Not Established
Carcinogenicity:	Not Established

12.- ECOLOGICAL INFORMATION

Eco Toxicity:	Not Established
Mobility:	Not Established
Biodegradation:	Not inherently biodegradable
Bio Accumulation:	Not Established

13.- DISPOSAL CONSIDERATIONS

General:	Seal all dust created by abrading in impervious bags and dispose to a suitable licensed landfill site
Disposal Methods:	Remove all packaging for recovery or incinerate/landfill

14.- TRANSPORT INFORMATION

Transport:	Not classified as dangerous for conveyance. Use any container of suitable size and length
-------------------	---

15.- REGULATORY INFORMATION

EEC Classification:	Not classified
Refer to:	Health & Safety at Work Act 1974 Control of Substances hazardous to Health (COSHH) Regulations 1994
Please note:	This Safety Data Sheet does not constitute the user's own assessment of workplace risk as required by other health and safety legislation.

16.- OTHER INFORMATION

Issued By:	Friction Technology LTD
Issue Date:	17/11/2017
Further Information:	<p>Health and Safety Executive Guidance Notes</p> <p>EH40/2000 - Occupational Exposure Limits 2000</p> <p>EH46 - Man-Made Mineral Fibres</p> <p>MDHS14 - General Methods for the Gravimetric Determination of Respirable and Total Inhalable Dust.</p> <p>MDHS59 - Man-Made Mineral Fibre</p>
Note:	<p>This information is based on our present knowledge and is accurate at the date of issue, to the best knowledge of Friction Technology Ltd. However, it shall not constitute a guarantee for any specific product featured and shall not establish a legally contractual relationship and condition or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage , use or disposal of the product.</p>