Mira Sport Electric Shower



COLD MAINS

YEAR WARRANTY

Enjoy long-lasting, powerful performance – from one of the UK's bestselling electric showers.

Product Information

Description	Colour	Product No.
Mira Sport 7.5 kW	White/Chrome	1.1746.820
Mira Sport 9.0 kW	White/Chrome	1.1746.821
Mira Sport 9.8 kW	White/Chrome	1.1746.822
Mira Sport 10.8 kW	White/Chrome	1.1746.824

Features & Benefits

Temperature control		
Advanced pressure stabilised temperature control		
Easy to fit		
Retrofits onto inlets of most Mira electric showers		
Adjustable slide bars fit over holes left by previous shower kit		
Easy to service		
Easy filter access		
For your customer		
Separate power and temperature controls		
Push button on/off		
Mira Sensi-flo [™] technology helps prevent scalding		
Mira Clearscale [™] and Dual Element [™] technology reduces limescale by up to 50%		
Phased shutdown flushes hot water from the tank making it safe for the next user		
4 spray 120 mm optimised showerhead with rub-clean nozzles		

Easy to clean smooth hose





Product Specification

Tech Details

Temperature control	Performance	
Control type: Advanced pressure stabilised	Temperature stability: ± 6°C	
Installation	Safety Features	
Power options: 7.5 kW 240V AC (6.9 kW 230V AC); 9.0 kW 240V AC (8.3 kW 230V AC); 9.8 kW 240V AC (9.0 kW 230V AC); 10.8 kW 240V AC (9.9 kW 230V AC)	Phased shutdown: Yes	
	Factory set to safe max temp: No	
Supply voltage: 230V ± 10%	Mira Sensi-flo [™] : Yes	
Supply rating: 32 amp (7.5 kW); 40 amp (9.0 kW); 45 amp (9.8 & 10.8 kW)	Accessories	
Terminal block connections: Maximum 16 mm ²	Wide range of accessories available at www.mirashowers.co.uk	
Water entry points: Left (rising, falling & rear)	Approvals	
Cable entry points: Left (rising, falling & rear)	BEAB approved	
Inlet connections: Brass inlet connector. 15 mm compression fitting	Kiwa certified	
Outlet connections: 1/2" BSP Male	WRAS approved	
Supply conditions	CE / UKCA marking	
Minimum maintained pressure: 7.5, 9.0 & 9.8 kW: 0.7 bar (7 metre head); 10.8 kW: 1.0 bar (10 metre head)		
Maximum maintained pressure: 5.0 bar (50 metre head)	Approved [certified] APPROVED PRODUCT N CA	

Dimensions

Maximum static pressure: 10.0 bar (100 metre head)





