




# Geberit Duofix element for shower, 130 cm, with wall drain, wall-mounted tap, concealed, for screed height at inlet 65–90 mm



## APPLICATION PURPOSES

- For metal and wood frame walls
- For Geberit Duofix system walls
- For installation in part- or room-height prewalls
- For installation in room-height partition walls
- For domestic bathrooms
- For receiving waste water from a single shower head
- For installation with a very low floor construction
- For drainage of floor-even showers
- For screed height  $\geq 65$  mm at inlet
- For concealed or surface-mounted taps
- For composite seals

## CHARACTERISTICS

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating
- With pull-out plate for lateral fastening above the element on metal or wood profiles or on Geberit Duofix system studs
- Alternative fastening point for wall anchors
- Rotating foot plates, suitable for installation in U profiles UW 50 and UW 75
- Foot plates that can be mounted in Geberit Duofix system rail without tools, without additional components

- Galvanised non-slip leg supports protected against corrosion
- Adjustable sealing level for tension-free sealing connection
- Self-adhesive sealing washer, fleece-laminated
- Premounted sealing fleece
- Sealing fleece, 10 cm circumferential, for connecting sealing systems
- Mounting plate adjustable in height and depth
- Mounting plate made of veneered wood, waterproof bonded
- Building material class B2 in accordance with DIN 4102-1, resp. class D-s2, d0 in accordance with EN 13501-3
- Formaldehyde release class A in accordance with EN 1084, resp. Class E 1 according to EN 13936
- Deviating from the requirements from EN 1253, the depth of water seal is just 30 mm
- Adjustable inlet height of trap
- Panelling thickness 10–40 mm
- Suitable for tile structures on floor 2–26 mm
- Suitable for tile structures on wall 2–35 mm
- Lateral drainage connection

## TECHNICAL DATA

Depth of water seal 30 mm

## SCOPE OF DELIVERY

- Straight connector made of PE-HD,  $\varnothing$  40 mm
- Elbow tap connector Rp 1/2" / R 1/2", compatible with MF
- Sealing washer
- Sound insulation base
- Insulating sleeve
- Protection box cover with integrated outlet sheet
- Fastening and protection material

## TO ORDER ADDITIONALLY

- Ready-to-fit set

## ACCESSORIES

- Geberit ready-to-fit set for wall drain, cover made of polished stainless steel
- Geberit ready-to-fit set for wall drain, cover made of brushed stainless steel
- Geberit ready-to-fit set for wall drain, cover made of stainless steel, screwable
- Geberit ready-to-fit set for wall drain, cover made of plastic
- Geberit ready-to-fit set for wall drain, tile-bearing, frameless
- Geberit ready-to-fit set for wall drain, tile-bearing, multi-piece
- Geberit collector profile for wall drain for shower

- Geberit shower board, tile-bearing, with V-slope
  - Geberit Duofix set of wall anchors for single installation
  - Geberit Duofix set of wall anchors for single installation, corner construction
- Geberit Duofix set of wall anchor extensions
  - Geberit Duofix system fastening bracket
  - Geberit Duofix fastening material for stud clearance 50–57.5 cm
  - Geberit Duofix set of foot fastener on rear wall
- Geberit Duofix set of foot extensions 20 cm length

**INFO**

- Natural stone tiles in the shower area may discolour

Art. no.	DN	d, ø mm	Discharge rate l/s	B cm	H cm	T cm
111.581.00.2	40	40	0.4	50	130	11
New						

New article available from 01.04.2025