

Geberit WC flush control with electronic flush actuation, mains operation, for Omega concealed cistern 12 cm, dual flush, for external button



Example image

Application purposes

- For manual remote flush actuation of Omega concealed cisterns 12
 cm using standard, potential-free push-buttons with closing function
- For releasing a single or dual flush
- For solid and drywall construction
- Suitable for less-abled installation
- For Omega concealed cisterns 12 cm

Characteristics

- Flush actuation connected by wire
- · Dual-flush remote control flush actuation via external push-buttons
- · Push-buttons can be connected in parallel
- Dual flush via flush plate can be triggered from above or from the front
- Can be combined with flush plates Omega20 to Omega60 or Geberit cover plates
- · Power supply via external power supply unit
- Transformation of mains voltage to extra-low voltage, 12 V DC
- · Operation with extra-low voltage, no mains voltage in cistern
- With push-fit connection with cross-polarity protection
- Interval flush preset
- Adjustable interval flush

- Device settings and operation with mobile device via integrated Bluetooth[®] interface
- Compatible with Geberit Control App
- · Wired networkable with Geberit gateway via GEBUS converter
- Wirelessly connectable with Geberit Gateway via Bluetooth[®]
- Compatible with Geberit Connect
- Low-noise lifting mechanism
- Electrical lifting device, self-calibrating

Technical data

| Protection degree | IP45 |
|---------------------------------------|-------------|
| Nominal voltage | 85-240 V AC |
| Mains frequency | 50-60 Hz |
| Operating voltage | 12 V DC |
| Power consumption | ≤ 4 W |
| Power consumption standby | 0.15 W |
| Interval flush, adjustment range | 1-168 h |
| Interval flush, factory setting | 24 h |
| Interval flush time, adjustment range | 1–200 s |
| Interval flush time, factory setting | 5 s |

- Scope of delivery
- Support block with servomotor and lifting device, premounted
- Electrical control

To order additionally

- Actuator plate or cover plate
- Push-button

Art. no. Material designation

_

115.955.00.6

- Connection cable, length 2 m, prefabricated
- Geberit Power & Connect box
- Geberit power supply unit for Power & Connect box