



APPLICATION PURPOSES

- For Geberit Duofix and Geberit GIS frames for wall-hung WC, with Sigma concealed cistern 12 cm
- For Geberit Duofix and Geberit GIS frames for wall-hung WC, with Omega concealed cistern 12 cm
- For supplying 12 V DC power to Geberit WC flush controls and Geberit DuoFresh modules
- For the power supply of Geberit hygiene flush units in concealed cisterns
- For preparing the mains connections of Geberit AquaClean shower toilets
- For hidden mains connection behind the WC ceramic appliance
- Not suitable for combining with fire protection set for Geberit Duofix element for wall-hung WC or fire protection for flush pipe and connection bend

CHARACTERISTICS

- 2025 range
- Can be installed without tools
- Separation of trades
- Power supply unit with LED display
- Connection cable with LED display
- Connection option for Geberit AquaClean
- Protection cover box for service opening protects against moisture and dirt

TECHNICAL DATA

Protection degree	IPX4
Nominal voltage	90–260 V AC
Mains frequency	50–60 Hz

Output voltage	12 V DC
Power	12 W

SCOPE OF DELIVERY

- Power & Connect Box
- Power supply unit with LED display
- Connection cable
- Intermediate bottom with terminal
- Protection box
- Conduit pipe, length 0.32 m, for connection of Geberit AquaClean

Art. no.

116.098.00.6

New

New article available from 01.01.2025