

# Geberit Monolith sanitary module for floor-standing WC, 114 cm, front cladding made of glass









Example image

#### **APPLICATION PURPOSES**

- · For floor inlets
- · For renovations, conversions and new buildings
- · For wall inlets with an inlet height of 18 cm
- For replacing floor-standing WCs with concealed cistern with maximum service opening height < 109 cm</li>
- · For replacing low-level exposed cisterns
- For replacing half-high level exposed cisterns
- For replacing floor-standing WCs with close-coupled exposed cistern
- For connecting Geberit AquaClean Tuma WC complete solution, floor-standing WC
- For connecting Geberit AquaClean WC enhancement solutions, with accessories
- · For replacing pressure flushing valves
- · For mounting on finished floors
- · For installation in front of drywalls or solid walls

#### **CHARACTERISTICS**

Dual flush

- · Compensation of dimensional tolerances possible
- · Cistern, fully insulated against condensation
- · Side cladding made of aluminium brushed
- · Self-supporting
- · Adjustable flush volume
- · Water supply connection on the rear centre
- Water supply connection on the left/right possible with accessories
- · Water supply connection on the bottom

#### **TECHNICAL DATA**

0.1–10 bar	Flow pressure
25 °C	Operating temperature, water
	max.
6/31	Flush volume, factory setting
4.5 / 6	Flush volume large, adjustment
	range
31	Flush volume small
9.6 l/min	Flow rate at 3 bar
0.5 bar	Minimum flow pressure
0.11 l/s	Calculated flow rate
	Calculated HOW rate

#### SCOPE OF DELIVERY

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend extension 160 mm
- · Connection bend made of PP, ø 90 mm
- Sleeve made of EPDM, ø 44 / 55 mm
- Adaptor socket made of PE-HD, ø 90 / 110 mm
- · Fastening material
- · Base cover
- · Fastening material for drywall

## **ACCESSORIES**

- Set of fixing bolts made of aluminium, for Geberit Monolith side cladding
- Conversion set for Geberit AquaClean WC enhancement solutions
- Lateral water supply connection set for Geberit Monolith sanitary module for WC

### **INFO**

· Glass thickness 8 mm



4r, no.	Colour Surface	<b>45</b>	# <sup>6</sup>	~ <sup>46</sup>
131.033.JK.5	Front cladding: lava glass Side cladding: black chrome aluminium	50.5	114	10.6
131.033.JL.5	Front cladding: sand grey glass Side cladding: aluminium	50.5	114	10.6
131.033.SI.5	Front cladding: white glass Side cladding: aluminium	50.5	114	10.6
131.033.SJ.6	Front cladding: black glass Side cladding: black chrome aluminium	50.5	114	10.6