



# Geberit Monolith Plus sanitary module for wall-hung WC, 114 cm, front cladding made of glass



Example image



## APPLICATION PURPOSES

- For renovations, conversions and new buildings
- For wall inlets with inlet height > 23 cm
- For replacing low-level exposed cisterns
- For replacing half-high level exposed cisterns
- For replacing wall-hung WCs with close-coupled exposed cistern
- For replacing wall-hung WCs with pressure flushing valve
- For replacing wall-hung WCs with concealed cistern with maximum service opening height < 109 cm
- For Geberit AquaClean WC complete solutions
- For connecting Geberit AquaClean WC enhancement solutions, with accessories
- For mounting on finished floors
- For installation in front of drywalls or solid walls
- For compensating the offset between WC connections and wall drains using a stepped straight connector for wall-hung WCs

## CHARACTERISTICS

- Dual flush
- Soft-touch buttons for flush actuation
- Settings can only be changed with the Geberit Home App
- User detection range can be set

- Odour extraction with ceramic honey comb filter can be activated
- Odour extraction unit with run-on function
- Ceramic honeycomb filter for odour neutralisation can be replaced without tools
- Adjustable interval flush
- With ComfortLight
- Lighting mood infinitely adjustable from orientation light to daylight
- Light colour continuously adjustable from warm white to cool white
- DALI-compatible control
- Operation with extra-low voltage, no mains voltage in cistern
- Mains connection with flexible three-core sheathed cable
- Water supply connection on the rear centre
- Water supply connection on the left/right possible with accessories
- Water supply connection on the bottom
- Compensation of dimensional tolerances possible
- Height-adjustable up to 7 cm
- Fastening height WC ceramic appliance  $35 \pm 1$  cm
- Cistern, fully insulated against condensation
- Side cladding made of aluminium brushed
- Self-supporting

## TECHNICAL DATA

Protection degree	IPX4
Nominal voltage	100–240 V AC
Operating voltage	12 V DC
Mains frequency	50–60 Hz
Power consumption standby max.	0.5 W
Flow pressure	0.1–10 bar
Operating temperature, water max.	25 °C
Flush volume, factory setting	6 / 3 l
Flush volume large, adjustment range	4–6 l
Flush volume small	3 l
Flow rate at 3 bar	9.6 l/min
Minimum flow pressure	0.5 bar
Calculated flow rate	0.11 l/s
Light colour	2200–4000 K

## SCOPE OF DELIVERY

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend extension 160 mm
- Sleeve made of EPDM,  $\varnothing 44 / 55$  mm
- Straight connector made of PE-HD,  $\varnothing 90$  mm



- Adaptor socket made of PE-HD, ø 90 / 110 mm
- 2 threaded rods M12
- Sound insulation set
- Female socket for mains connection
- Power supply unit
- Base cover
- Fastening material for drywall
- Fastening material

- Fastening material for installation in front of concealed cisterns

#### ACCESSORIES

- Geberit straight connector set for wall-hung WC, stepped by 3 cm
- Geberit straight connector set for wall-hung WC, stepped by 5 cm

- Geberit straight connector set for wall-hung WC, stepped by 7 cm
- Conversion set for Geberit AquaClean WC enhancement solutions
- Lateral water supply connection set for Geberit Monolith sanitary module for WC
- Geberit outlet mounting box
- Interface module 12 V for Geberit AquaClean Mera/Sela

Art. no.	Colour / surface	B cm	H cm	T cm	Protection class	Power consumption W
<b>131.231.JK.7</b>	Front cladding: lava glass Side cladding: black chrome aluminium	50.5	114	10.6	I	15
<b>131.231.JL.7</b>	Front cladding: sand grey glass Side cladding: aluminium	50.5	114	10.6	I	15
<b>131.231.SI.7</b>	Front cladding: white glass Side cladding: aluminium	50.5	114	10.6	I	15
<b>131.231.SJ.7</b>	Front cladding: black glass Side cladding: black chrome aluminium	50.5	114	10.6	I	15