

Geberit Duofix element for wall-hung WC, 82 cm, with Alpha concealed cistern 12 cm, 6/3 litres, Alpha01 flush plate, square









APPLICATION PURPOSES

- · For metal and wood frame walls
- · For installation in part-height prewalls
- For floor constructions 0–20 cm
- · For wall-hung WCs

CHARACTERISTICS

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating
- Frame for wall-hung WCs with connection dimensions as per EN 33 and projection up to 62 cm
- Frame with ø 9 mm drilling holes for fastening in wood frame construction
- Foot plates made of plastic
- Foot plate depth suitable for installation in U-profiles UW 50
- · Galvanised leg supports protected against corrosion
- Connection bend can be mounted without tools
- Geberit Alpha concealed cistern 12 cm fully insulated against condensation

- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- · For top or front actuation, suitable for dual flush
- Immediate post flush possible with factory setting
- · Water supply connection on the left
- Protection box for service opening, can be cut to length, protects against moisture and dirt
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- · Fastening option for electrical connection

TECHNICAL DATA

| Flow pressure | 0.1–10 bar |
|--------------------------------|--------------|
| Operating temperature, water | 25 °C |
| max. | |
| Flush volume, factory setting | 5.8/31 |
| Flush volume large, adjustment | 4/4.5/6/7.51 |
| range | |
| Flush volume small, adjustment | 2-41 |
| range | |
| Button shape | square |
| | |

Product material

Steel

SCOPE OF DELIVERY

- Water supply connection R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and hand wheel
- · Protection box for service opening
- · 2 wall anchors
- Geberit Alpha01 (ex Alpha30) flush plate for dual flush, square
- Connection set for WC, ø 90 mm
- Connection bend 90° made of PE-HD, ø 90 mm
- Geberit pull disc for Type 212 flush valve for Omega concealed cistern 82 cm
- Adaptor socket made of PE-HD, ø 90 / 110 mm
- Fastening and protection material

ACCESSORIES

- · Geberit Duofix set of foot fastener on rear wall
- Geberit set of support brackets for WC ceramic appliances with small contact surfaces
- · Geberit sound insulation set for wall-hung WC
- · Geberit Duofix set of foot extensions 20 cm length



| An no. | Colour/surface | & CD | # % | ~ E |
|-----------------|----------------|------|--------|-----|
| 8.034.21.2 w | chrom / glossy | 50 | 82 | 14 |

New article available from 01.05.2025