Product Data Sheet



415 370 side screw fixing centres inlet → 150 ⊢ | -- 210 --option screw fixing centres 35-+-275 285 fixing 195 front screws 85 bottom delayed fill inlet option bottom inlet option +170 +170 + /35

Conceala 2 Cistern Universal Height 6 Litre Valve Side Supply

Illustrated

S3622 Conceala 2 cistern 6 litre single flush valve side supply and internal overflow, alternative height plastic

flushbends, no push button

S4512 Finger push button pneumatic, stainless steel for 31mm

maximum thickness partition

Configuration options

S4513 Palm push button Pneumatic, stainless steel for 31mm

maximum thickness partition

S4464 Finger push button pneumatic, plastic for 31mm maximum

thickness partition

S4463 Palm push button Pneumatic, plastic for 31mm maximum

thickness partition

S4489 Finger push button pneumatic, stainless steel body for

.....

400mm maximum wall thickness

SV316 3 metre tube

Material

Plastic

Weights

S3622 3.00KG S4512 0.71KG

Colours

Neutral / No Finish (67)

Standards

Cistern to BS EN 14055

Special Notes

Cistern is supplied with 800mm length of plastic air tube. An optional 3m length can be purchased where remote operation is required.

Capacity

Frequently used applications

Education Factory General Healthcare Hospitals Office Hotels

Public Building Pubs and Clubs

Residential Retail

Sports and Leisure



Email: info@idealspec.co.uk Tel: 0870 122 8822 Fax: 0870 122 8282

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Web: www.idealspec.co.uk



Date created: 30/03/2016