# Technical Data Sheet

## Full height cupboard unit, slim and standard depth

What's in the box: 1x F2FHU3.X, F3FHU3.X + fixings



#### Materials

Carcass: 16mm MFC

- Dimensions are subject to change, customers are advised to measure actual product before commencing installation.
- Fixing point dimensions are for guidance only/the positions of wall fixing must be checked when product is received.
- Legs provide height adjustment range of 75mm (included in the box, but not shown in the diagram).
- Care should be taken when calculating configurations without filler/end panels.

### FAQs

Q: How do I fix the unit to the wall?

- Q: Are the fascia/ door packs included?
- Q: Is the shelf removable?
- Q: When the doors are open, how wide is the unit?
- Q: Why are there redundant holes on top panel of carcass?
- Q: How do I apply a Legacy (traditional/ stepped) plinth?

Q: Why can't I adjust the wall hanging mechanisms when unit is off the wall?

Q: What material is the shelf?

A: There are adjustable wall hangers installed in the unit and wall plate kit is provided.

TAVISTO

A: No, these will need to be ordered separately - please see brochure for reference.

- A: There are 3 adjustable shelves and one fixed shelf.
- A: For the standard depth unit, 635mm. For the slim depth unit, 327mm

A: The base and top panel are universal for efficiency reasons- they are not to be used. When worktop is applied these holes will be covered.

A: Follow instructions (provided upon request). Ensure adjustable leg is orientated correctly, plinth is in-line with front face of door fascia & plinth clips are used to step-off sufficiently.

A: The mechanism requires weight/pressure applied to enable adjustment. Follow diagram in instructions for adjustment details.

A. 16mm MFC, held in position with shelf pins. Shelves are adjustable at a 64mm height increment.

#### NOTE: Colours unique to Tavistock - No RAL Code available

Diagrams not to scale All dimensions in mm Tolerance of +/-5mm