





Corsa Z Stroke Z [mm] Course Z	Lz [mm]	L1 [mm]	L2 [mm]	L3,min [mm]	L3,max [mm]	Portata Z Payload Z [kg] Charge Z
500	550	590	886	360	610	30
600	600	640	936	360	660	30
700	650	690	986	360	710	29
800	700	740	1036	360	760	29
900	750	790	1086	360	810	28
1000	800	840	1136	360	860	28
1100	850	890	1186	360	910	27
1200	900	940	1236	360	960	27
1300	950	990	1286	360	1010	26
1400	1000	1040	1336	360	1060	26
1500	1050	1090	1386	360	1110	25

IT

Il sistema verticale telescopico è stato studiato per venire incontro alle richieste di massima corsa verticale in locali con altezze ridotte.

Le due guide che si sovrappongono scendono contemporaneamente comandate da un unico motoriduttore e la trasmissione è affidata a cinghie AT10/25.

I carichi massimi e le corse applicabili sono riportate nella tabella allegata

EN

Vertical Telescopic system has been studied to satisfy requests of maximum vertical stroke in low height locations.

Two overlapped guides go down simultaneously, controlled by one reduction unit and transmission has been provided by belt AT10/25.

Maximum loads and stroke are explained in the table above.