Nr.	Title	Descrizione	Type/Model	Serial Number	Year of Construction	Technical Data
1	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. coclea di carico	CCL TR 300 23	3110-028-0115	2015	diameter screw: 280 mm, tier: 250 mm, elevating height: 1650 mm, total dimensions: 2200 mm x 750 mm x 1850 mm.
2	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. coclea inclinata lunga	CCL -TR 300/09	3110-023-0115	2005	diameter screw: 290 mm, tier: 220 mm, elevating height: 4800 mm, total dimensions: 6000 mm x 1600 mm x 5000 mm.
3	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. coclea di scarico	CCL-TR400/7	3110-014-0115	2015	dimensions: 6500 mm x 1200 mm x 2500 mm.
4	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. vasca con nastro di pre-lavaggio con filtro	VS-PRV 600/2	3640-006-0115	2015	plastic mesh elevating belt, belt width: 600 mm, divider height: 100 mm, distance between dividers: 260 mm, elevating height: 1550 mm, total dimensions: 3650 mm x 1800 mm x 1650 mm.
5	MBS s.r.l.	MBS s.r.l. scambiatore di calore tubolare	MLI 168 2000 BA	12463	2015	volume: 19.26/17.91 liter, design pressure: 10 bar, minimum temperature: -10°C, maximum temperature: 110°C, dimensions: 2000 mm x 280 mm x 280 mm.
6	De Nora Next	De Nora Next impianto trattamento acqua UV-OZONO	UV 80/3 G RACK LCD			230 V, 50/60 Hz, 240 W, 9 bar, dimensions: 1600 mm x 650 mm x 1400 mm.
7	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. vasca con nastro di lavaggio intensivo con filtro	VS-TBM 600/2	3640-007-0115	2015	plastic mesh elevating belt with dividers, belt width: 600 mm, divider height: 100 mm, distance between dividers: 250 mm, elevating height: 2100 mm, total dimensions: 4200 mm x 1800 mm x 2300 mm.
8	MBS s.r.l.	MBS s.r.l. scambiatore di calore tubolare	MLI 168 2000 BA	12464	2015	volume: 19.26/17.91 liter, design pressure: 10 bar, minimum temperature: -10°C, maximum temperature: 110°C, dimensions: 2000 mm x 280 mm x 280 mm.
9	De Nora Next	De Nora Next UV impianto trattamento acqua UV-OZONO	UV 80/3 G RACK LCD			230 V, 50/60 Hz, 240 W, 9 bar, dimensions: 1600 mm x 650 mm x 1400 mm.
10	Siemens	quadro elettrico in acciaio inox con pannello di controllo Siemens.				dimensions: 450 mm x 300 mm x 450 mm.
11	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro elevatore	NS RT 400/35	3270-017-0115	2015	plastic mesh belt, belt width: 600 mm, elevating height: 2150 mm, total dimensions: 3600 mm x 1100 mm x 2300 mm.
12	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro divisore di linea con celle di pesatura	NS RT 400/24	3270-016-0115	2015	plastic mesh belt, belt width: 350 mm, total dimensions: 2400 mm x 1000 mm x 550 mm.
13	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro trasportatore				plastic mesh belt, belt width: 400 mm, total dimensions: 2450 mm x 900 mm x 1500 mm.
14	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. centrifuga	VENUSIA EVU 316	3086-008-0215	2015	diameter drum: 550 mm, height: 500 mm, total dimensions: 1350 mm x 1050 mm x 1350 mm.
15	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro elevatore				plastic mesh belt with dividers, belt width: 450 mm, divider height: 25 mm, distance between dividers: 210 mm, elevating height: 1150 mm, total dimensions: 1600 mm x 700 mm x 1300 mm.
16	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro trasportatore				plastic mesh belt, belt width: 400 mm, total dimensions: 2450 mm x 900 mm x 1500 mm.
17	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. centrifuga	VENUSIA EV03162015	3086-008-0115	2015	diameter drum: 550 mm, height: 500 mm, total dimensions: 1350 mm x 1050 mm x 1350 mm.
18	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro elevaotre				plastic mesh belt width dividers, belt width: 450 mm, divider height: 25 mm, distance between dividers: 210 mm, elevating height: 1150 mm, total dimensions: 1600 mm x 700 mm x 1300 mm.
19	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. tavolo vibrante	IV VB 500/18	3530-004-0115	2015	gutter width: 530 mm, total dimensions: 1530 mm x 1200 mm x 1000 mm.
20	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro trasportatore	NS RT 600/65	3270-018-0115	2015	plastic mesh belt, belt width: 530 mm, total dimensions: 6800 mm x 950 mm x 1350 mm.

Nr.	Title	Descrizione	Type/Model	Serial Number	Year of Construction	Technical Data
21	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro trasportatore	NS RT 600/65	3270-015-115	2015	plastic mesh belt, belt width: 530 mm, total dimensions: 6750 mm x 970 mm x 1500 mm.
22	Siemens	quadro elettrico in acciaio inox con pannello di controllo Siemens				dimensions: 450 mm x 300 mm x 450 mm.
23	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro elevatore				plastic mesh belt with dividers, belt width: 320 mm, divider height: 20 mm, distance between dividers: 600 mm, elevating height: 4050 mm, total dimensions: 6300 mm x 680 mm x 4200 mm.
24	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. nastro trasportatore				plastic mesh belt, belt width: 310 mm, total dimensions: 2600 mm x 500 mm x 350 mm/
25	Comek	Comek 10- pesatrice multitesta a 10 teste	CK10ST	0545	2015	type: PESATRICE MULTITESTA, 120 V, 50-60 Hz, 2 kW, 8 A, weight: 500 kg, dimensions: 1400 mm x 1350 mm x 2750 mm. Including s/s tub and plastic bin with parts.
26	NN denester	disimpilatore vaschette				diameter trays: 200 mm, total dimensions: 700 mm x 600 mm x 1800 mm.
27	NN transport belt	nastro trasportatore disimpilatore				plastic belt, belt width: 200 mm, total dimensions: 3650 mm x 500 mm x 1250 mm.
28	Comek	Riempitrice Comek con nastro di alimentazione in ingresso e nastro di uscita	SIST. ROTATIVO A PASSO	0547	2015	type: RIEMPITRICE, 400 V, 3 Ph, 50 Hz, 10 A, 4 kW, 8 stations, diameter cups: 200 mm, total dimensions filling machine: 1200 mm x 1300 mm x 1800 mm, total length belt: 8000 mm.
29	NN platform	Piattaforma in acciaio inox con scala				working height: 2300 mm, total dimensions: 4200 mm x 2300 mm x 3350 mm.
30	NN line dividing belt	nastro di suddivisione linea con tappeto modulare in plastica				belt width: 450 mm, total dimensions: 1500 mm x 1000 mm x 1550 mm.
31	Italian Pack Yang s.r.l.	Italian Pack Yang s.r.l. termosigillatrice	POLVR300RI2U2MA21BF IFpv5g	149108	2014	400 V, 3 Ph, 50 Hz, 12.1 kW, weight: 900 kg, film width: 490 mm, diameter dye: (2x) 200 mm, plastic outfeed belt, belt width: 550 mm, total dimensions: 4050 mm x 1000 mm x 1750 mm.
32	NN transport belt	Nastro trasportatore				plastic belt, belt width: 110 mm, total dimensions: 1200 mm x 500 mm x 930 mm.
33	Idecon s.r.l.	Idecon s.r.l. controllo peso dinamico con espulsore	WP-3000	ID 00470		230 V, 50 Hz, 0.5 kW, maximum weight: 3000 g, minimum weight: 40 g, plastic belt, belt width: 240 mm, total dimensions: 900 mm x 750 mm x 1800 mm.
34	Comek	Comek s/s tavolo rotante				diameter: 1200 mm, height: 1000 mm.
35	NN transport belt	Nastro trasportatore				plastic belt, belt width: 110 mm, total dimensions: 1750 mm x 350 mm x 1000 mm.
36	Cosmo Food Machinery s.r.l.	Cosmo Food Machinery s.r.l. s/s quadro elettrico generale	LZ-0R469/28000	0075-0025-0115	2015	dimensions: 1200 mm x 420 mm x 2400 mm.
37	Sormac	Tramoggia di alimentazione con nastro di uscita		VBK-2020	2014	230/400 V, 50 Hz, 0.37 kW, plastic belt, belt width: 500 mm, total dimensions: 3500 mm x 2200 mm x 2350 mm.