

RENIO

arcluce.it  renio



APPARECCHIO

- Corpo in tecnopolimero rinforzato in fibra di vetro, infrangibile.
- Cornice o frangiluce in alluminio pressofuso (EN 47100) o acciaio inox AISI 316L.
- Verniciatura a polvere poliestere in doppio strato stabilizzata ai raggi UV, resistente alla corrosione e alle nebbie saline.
- Guarnizioni in gomma siliconica.
- Viteria esterna in acciaio inox AISI 316.
- Schermo in policarbonato rigato e sabbato internamente per ridurre l'abbagliamento, liscio esternamente per facilitare la pulizia.
- Apparecchio costruito in conformità alle norme EN 60598-1 e EN 60598-2-2.

SORGENTE

- LED con efficienza nominale sino a 150lumen/Watt (4000K - 60mA - CRI>80 - Tj=85°C).
- Lunga vita utile del LED: > 50000h con L80.
- Alta consistenza dei colori: <3 SDCM.
- Disponibili versioni con lampade tradizionali.

INSTALLAZIONE

- Installazione ad incasso.
- Doppio passacavo stagno per collegamento in cascata.
- Controcassa in tecnopolimero.

Questi apparecchi sono predisposti per i moderni sistemi di controllo. Per le diverse possibilità vedi la sezione "Controllo della luce".

LUMINAIRE

- Shatterproof body made of fiber glass reinforced engineering plastic.
- Die-cast aluminium (EN 47100) or AISI 316L stainless steel trim or louver.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Ribbed and internally frosted polycarbonate diffuser to reduce glare, smooth outside surface to ease cleaning.
- It complies with standards EN 60598-1 and EN 60598-2-2.




SOURCE

- Nominal LED efficacy up to 150lumen/Watt (4000K - 60mA - CRI>80 - Tj=85°C).
- LED life time: >50000h with L80.
- High colour consistency: <3 SDCM.
- Available with conventional lamps.

INSTALLATION

- Recessed installation.
- Double waterproof grommet for through wiring.
- Recessed installation box made of engineering plastic.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".



RENIO

Cornice in alluminio pressofuso - Die-cast aluminium trim

arcluce.it  renio

Schermo in policarbonato opale. Completo di controcassa in materiale termoplastico (Q7739).

Opal polycarbonate screen. Supplied with recessed installation box made of engineering plastic (Q7739).


☐ 11 ☒ 12 ☐ 21



Code	WATT	SC	CEI	Source lumen	Luminaire lumen	K	CRI	Class
Q7746 *	18W LED		•	900	430	3000	80	⊕
Q7747 *	18W LED		•	1200	580	4000	80	⊕
Q7721	1x 18W FSD 2G11		•	1200		4000	80	⊞
Q7722 **	1x 20W FSM-E E27		•					⊞

** Lampada non inclusa. - Lamp not included.

IP65



* Driver LED incluso.


* LED driver included.



Code	WATT	SC	CEI	Source lumen	Luminaire lumen	K	CRI	Class
Q7748 *	18W LED		•	900	130	3000	80	⊕
Q7723 *	18W LED		•	1200	170	4000	80	⊕
Q7725	1x 18W FSD 2G11		•	1200		4000	80	⊞
Q7726 **	1x 20W FSM-E E27		•					⊞

** Lampada non inclusa. - Lamp not included.

IP65




* Driver LED incluso.

* LED driver included.



Code	WATT	CEI	Source lumen	Luminaire lumen	K	CRI	Class
Q7727 *	18W LED	•	900	210	3000	80	⊕
Q7728 *	18W LED	•	1200	280	4000	80	⊕
Q7729	1x 18W FSD 2G11	•	1200		4000	80	⊞

IP65



* Driver LED incluso.

* LED driver included.

RENIO

Cornice in acciaio inox AISI 316L - AISI 316L stainless steel frame above ground

arcluce.it  renio

Schermo in policarbonato opale. Completo di controcassa in materiale termoplastico (Q7739).

Opal polycarbonate screen. Supplied with recessed installation box made of engineering plastic (Q7739).


 30



Code	WATT	CEI	Source lumen	Luminaire lumen	K	CRI	Class
Q7730 *	18W LED	•	900	430	3000	80	⊕
Q7731 *	18W LED	•	1200	580	4000	80	⊕
Q7733	1x 18W FSD 2G11	•	1200		4000	80	⊕
Q7734 **	1x 20W FSM-E E27	•					⊕

** Lampada non inclusa. - Lamp not included.

IP65




* Driver LED incluso.

* LED driver included.



Code	WATT	CEI	Source lumen	Luminaire lumen	K	CRI	Class
Q7735 *	18W LED	•	900	210	3000	80	⊕
Q7736 *	18W LED	•	1200	280	4000	80	⊕
Q7737	1x 18W FSD 2G11	•	1200		4000	80	⊕

IP65



* Driver LED incluso.

* LED driver included.

Accessori - Accessories

Per poter predisporre in anticipo l'installazione, è possibile ordinare separatamente la controcassa da interrare. L'apparecchio potrà essere ordinato successivamente e verrà comunque fornito completo di controcassa (da eliminare se acquistato separatamente in precedenza).

It is possible to purchase the recessed box separately, whenever it is necessary to start the installation in advance. The item can be ordered later on and it will be supplied complete with recessed box (to be removed if purchased separately in advance).



Cassetta da incasso in materiale termoplastico.
Thermoplastic material recessed installation box.

Code	Kg
Q7739	0,20

