

Step lights

THUNDER180

arcluce-us.com 🔍 thunder



DESCRIPTION

Luminaire

- Die-cast aluminium body (EN 47100).
- Die-cast aluminium (EN 47100) or AISI 316L stainless steel trim.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5/16" thermal-shock resistant tempered glass.

Electrical

- Nominal LED efficacy up to 133lm/W (4000K - 350mA - CRI>80 - (Tj 100°C)).
- LED life time: 50000h - L80 - B20.
- High colour consistency: <3 SDCM.

Installation

- Recessed installation.
- PG11 engineering plastic cable gland.
- Supplied with power cable (10').
- Recessed installation box made of engineering plastic.

Amber color LED on request.

TECHNICAL INFORMATION

Luminaire power:	14W
Source lumen:	1550lm
LED:	3000K - 4000K, CRI>80



THUNDER180




Family	Model	Size	Trim type	Optics	CCT	Fixture color	Wiring
Q- Wall recessed	TH Thunder	5 7"	7 Aluminium louvred	7 Asytmmetrical	3 3000K	US- 16 Grey	S 120-277V 60Hz / 0-10V
					4 4000K	US- 21 Aluminium	



Trim type

7



Die-cast aluminium louvred

Weight: 3,66 lb

Accessories

It is possible to purchase the recessed box separately, whenever it is necessary to start the installation in advance. The item can be ordered at a later time, and it will be supplied complete with recessed box (to be removed if purchased separately in advance).



Code	lb
1099237X	0.44

Thermoplastic material recessed installation box.

