

KOMPASS

arcluce.it  kompass



LUMINAIRE

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 8mm thermal-shock resistant tempered glass.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- It complies with standards EN 60598-1 and EN 60598-2-1.

INSTALLATION

- Wall mounted.
- Die-cast aluminium base plate (EN 47100).
- Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

These fittings are suitable for the modern control systems.
For the various possibilities, please see section "Controlling the light".

STANDARD PRODUCT		AVAILABLE OPTIONS	
Wiring	ON/OFF (A)		
CCT	4000K (-840)	3000K (-830)	
Colour	<input checked="" type="radio"/> 16	<input type="radio"/> 21	



KOMPASS


arcluce.it  kompass





STANDARD COLOUR

● 16

DIMENSIONS



Code	Optic	Luminaire	CCT	CRI	Class	Wiring	Power Supply	A mm	B mm	C mm
0473000A-840-16	 very-wide flood 72°	20W, 1250lm	4000K	80	⊕	ON/OFF	220-240V 50/60Hz	102	150	491
0473001A-840-16	 very-wide flood 72°	39W, 2500lm	4000K	80	⊕	ON/OFF	220-240V 50/60Hz	102	150	784

The **photo** represents the family product range. You can see the correct image of each product (code) on the website.

LED driver included.

