

N-SERIES

Specification Sheet

NPS 300 CREW



www.isuzu.co.za f t

ISUZU

With you, for the long run

MODEL	NPS 300 CREW CAB
AXLE LAYOUT	4X4
CONTROL	FORWARD
MASS	
Permissible Body + Payload (kg)	3150
Tare - Total (T) (kg)	3050
Tare - Front (kg)	1830
Tare - Rear (kg)	960
GVM (kg)	6200
V (kg)	6200
GCM (kg)	9500
D/T (kg)	9500
Axle - Front GA/GAU (kg)	2800
Axle - Front A/AU (kg)	2800
Axle - Rear GA/GAU (kg)	6600
Axle - Rear A/AU (kg)	5600
Litres of Fuel Tank 1 Included in Tare (litres)	15
Litres of Fuel Tank 2 Included in Tare (litres)	0
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
PERFORMANCE	HIGH & LOW RATIO
Gradeability at V (%)	43/80
Gradeability at D/T (%)	27/50
Max. Geared Road Speed (km/h)	104
MAJOR DIMENSIONS	
OL - Overall Length (mm)	5985
OW - Overall Width (mm)	1995
WB - Wheelbase (mm)	3395
CA - Cab to Bogie/Rear Axle (mm)	1821
CE - Cab to End of Chassis (mm)	3301
OH - Overall Height (mm)	2265
FOH - Front Overhang (mm)	1110
ROH - Rear Overhang (mm)	1510
EH - Chassis Rear End Height (mm)	975
HH - Ground Clearance (mm)	210

MODEL	NPS 300 CREW CAB
AXLE LAYOUT	4X4
CONTROL	FORWARD
MAJOR DIMENSIONS	
Chassis Width - Rear (mm)	850
Turning Radius - Curb to Curb (mm)	6450
Turning Radius - Wall to Wall (mm)	7200
ENGINE	
Make	Isuzu
Model	4HK1-TCN
Capacity (cm ³)	5193
Layout	Diesel Inline 4
Type	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	110 @ 2600
Torque @ r/min (Nm)	404 @ 1500 - 2600
Emissions Standard	Euro 2
CLUTCH	
Make	Exedy
Model	325
Type	Single
Diameter (mm)	325
Operation	Hydraulic-Assisted
TRANSMISSION	
Make	Isuzu
Model	MYY5T
Type	5-Speed Synchronesh
Shift	Manual Gearshift
No. of Gears Forward	5
First Gear Ratio : 1	5.315 H / 9.790 L
Top Gear Ratio : 1	0.721 H / 1.328 L
Transfer Case	Yes
PTO (Power Take-Off)	Optional
DRIVE AXLE	
Make	Isuzu
Model Axle Front	FD028

MODEL	NPS 300 CREW CAB
AXLE LAYOUT	4X4
CONTROL	FORWARD
DRIVE AXLE	
Model Drive Axle Rear	R066
Reduction Type	Single
Final Ratio : 1	5.125
SUSPENSION	
Front	Semi-Elliptic Springs
Rear	Semi-Elliptic Springs
Shock Absorbers	Front & Rear
Stabilisers	Yes
STEERING	
Operation	Power
BRAKES	
System Type	Vacuum Hydraulic
Front	Drums
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Drum on Propshaft
Exhaust Brake	Standard
ELECTRICAL & FUEL	
Fuel Tank 1 Capacity (litres)	100
Fuel Tank 2 Capacity (litres)	0
TYRES	
Size & Ply Rating - Front	7.50 R16-12PR
Size & Ply Rating - Rear	7.50 R16-12PR
CAB & EXTRAS	
Type	Crew
Roof	Low
No. of Bunks	0
No. of Seats (Lap Rear & Centre)	7
Air-Conditioning	Optional
Radio	Optional
Tilt Cab	No

The information above is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Model/s shown may differ. E&OE. Date of print December 2017