



OPTIMO H426



M-Code	Size	LI	SR	USE	PR	S/W Type	Recom- mended Rim	Max. Air (PSI)	Max.Load		Overall Diameter		Section Width		Tread Width		Tread Depth		SLR	RPM	Rolling Circum- ference
									(kgs)	(lbs)	mm	inch	mm	inch	mm	inch	mm	inch (32")			
80																					
1012695	155/80R13	79	T	J	4	RSB	4.5	44	437	963	574	22.6	160	6.3	106	4.2	7.6	9.6	919	1751	
70																					
1012694	155/70R13	75	T	J	4	RSB	4.5	44	387	853	548	21.6	157	6.2	114	4.5	7.2	9.0	963	1671	
1012663	165/70R14	81	T	J	4	RSB	5.0	44	462	1019	588	23.1	170	6.7	116	4.6	7.4	9.3	897	1793	
1011738	175/70R14	84	T	CK	4	RSB	5.0	44	500	1102	603	23.7	180	7.1	122	4.8	8.0	10.1	875	1839	
1011739	175/70R14	84	T	CI	4	RSB	5.0	44	500	1102	603	23.7	180	7.1	122	4.8	8.0	10.1	875	1839	
1012666	175/70R14	84	T	J	4	RSB	5.0	44	500	1102	599	23.6	181	7.1	122	4.8	7.8	9.8	880	1828	
1012697	185/70R14	88	T	J	4	RSB	5.5	44	560	1235	613	24.1	193	7.6	126	5.0	8.0	10.1	860	1871	
1012699	205/70R15	96	T	J	4	RSB	6.0	44	710	1565	669	26.3	209	8.2	140	5.5	7.8	9.8	789	2040	
1006709	215/70R15	98	H	C-	4	RSB	6.5	44	750	1653	683	26.9	222	8.7	164	6.5	8.3	10.5	773	2083	
1011135	215/70R16	100	H	CH	4	RSB	6.5	44	800	1764	703	27.7	217	8.5	162	6.4	8.5	10.7	751	2144	
65																					
1012819	155/65R13	73	T	J	4	RSB	4.5	44	365	805	532	20.9	157	6.2	114	4.5	7.2	9.0	992	1623	
1012696	165/65R13	77	T	J	4	RSB	5.0	44	412	908	541	21.3	181	7.1	122	4.8	7.8	9.8	975	1650	
1012662	155/65R14	75	S	J	4	RSB	4.5	44	387	853	558	22.0	157	6.2	114	4.5	7.2	9.0	946	1702	
1012643	175/65R14	82	H	-	4	RSB	5.0	44	475	1047	584	23.0	177	7.0	144	5.7	7.5	9.4	903	1781	
1012665	175/65R14	82	H	J	4	RSB	5.0	44	475	1047	584	23.0	177	7.0	144	5.7	7.5	9.4	903	1781	
1006703	185/65R14	86	H	CH	4	RSB	5.5	44	530	1168	592	23.3	196	7.7	132	5.2	8.0	10.1	891	1806	
1012667	185/65R14	86	H	J	4	RSB	5.5	44	530	1168	594	23.4	198	7.8	136	5.4	8.0	10.1	888	1813	
1012698	195/65R14	89	H	J	4	RSB	6.0	44	580	1279	607	23.9	208	8.2	144	5.7	8.0	10.1	869	1853	
1010721	P185/65R14	85	H	CI	4	RSB	5.5	44	510	1124	592	23.3	196	7.7	132	5.2	8.0	10.1	891	1806	
1011292	175/65R15	84	H	-	4	RSB	5.0	44	500	1102	609	24.0	177	7.0	144	5.7	7.5	9.4	866	1857	
1009943	185/65R15	88	T	CH	4	RSB	5.5	44	560	1235	621	24.4	194	7.6	136	5.4	8.0	10.1	850	1894	
1012644	185/65R15	88	H	-	4	RSB	5.5	44	560	1235	617	24.3	189	7.4	134	5.3	7.6	9.5	855	1882	
1012654	185/65R15	88	H	J	4	RSB	5.5	44	560	1235	617	24.3	189	7.4	148	5.8	7.6	9.5	855	1882	
1011161	195/65R15	91	H	V	4	RSB					630	24.8	207	8.1	148	5.8	8.0	10.1	838	1922	
1009944	195/65R15	91	T	CH	4	RSB	6.0	44	615	1356	633	24.9	204	8.0	148	5.8	8.0	10.1	834	1931	
1010212	195/65R15	91	T	S	4	RSB	6.5	44	615	1356	634	25.0	207	8.1	148	5.8	7.8	9.7	832	1934	
1011297	195/65R15	91	H	-	4	RSB	6.0	44	615	1356	635	25.0	201	7.9	148	5.8	7.6	9.5	831	1937	
1012655	195/65R15	91	H	J	4	RSB	6.0	44	615	1356	634	25.0	201	7.9	148	5.8	7.6	9.5	832	1934	
1012851	195/65R15	91	S	J	4	RSB					632	24.9	208	8.2	146	5.7	8.0	10.1	835	1928	
1013068	195/65R15	91	T	CR	4	RSB	6.0	44	615	1356	633	24.9	204	8.0	148	5.8	8.0	10.1	834	1931	
1012459	205/65R15	94	H	S	4	RSB	6.0	44	635	1400	643	25.3	212	8.3	152	6.0	8.3	10.5	821	1961	
1006707	205/65R15	94	V	C-	4	RSB	6.0	44	670	1477	647	25.5	214	8.4	156	6.1	8.3	10.5	816	1973	
1012700	215/65R15	96	H	J	4	RSB	6.5	44	710	1565	661	26.0	220	8.7	160	6.3	7.8	9.8	798	2016	
1006221	215/65R15	96	V	CH	4	RSB	6.5	44	710	1565	633	26.1	226	8.9	162	6.4	8.0	10.1	796	2022	
1011021	215/65R15	XL 100	CR	4	RSB	6.5	50	800	1764	663	26.1	226	8.9	162	6.4	8.0	10.1	796	2022		
1006260	P185/65R15	86	T	H	4	RSB	5.5	44	530	1168	620	24.4	185	7.3	134	5.3	7.8	9.7	288	851	1891
1010376	P185/65R15	86	T	I	4	RSB	5.5	44	530	1168	618	24.3	185	7.3	134	5.3	7.8	9.7	286	854	1885
1006261	P195/65R15	89	T	H	4	RSB	5.5	44	580	1279	636	25.0	192	7.6	148	5.8	7.8	9.7	296	830	1940
1010011	P195/65R15	89	T	K	4	RSB	6.5	44	580	1279	674	26.5	214	8.4	148	5.8	7.8	9.7	304	783	2054
1010199	P195/65R15	89	S	I	4	RSB	6.0	44	580	1279	634	25.0	201	7.9	148	5.8	7.8	9.7	295	832	1935
1010208	P195/65R15	89	S	T	4	RSB	6.0	44	580	1279	633	24.9	202	7.9	148	5.8	7.8	9.7	296	834	1929
1010377	P195/65R15	89	T	I	4	RSB	5.5	44	580	1279	635	25.0	196	7.7	148	5.8	7.8	9.7	296	831	1937
1011606	P195/65R15	89	S	J	4	RSB					632	24.9	208	8.2	146	5.7	8.0	10.1	835	1928	
1011354	P195/65R15	89	T	T	4	RSB	6.0	44	580	1279	635	25.0	201	7.9	148	5.8	7.8	9.8	295	831	1937
1011363	P195/65R15	89	T	U	4	RSB	6.0	44	580	1279	635	25.0	201	7.9	148	5.8	7.8	9.8	295	831	1937
1006358	P205/65R15	92	H	K	4	RSB	6.0	44	635	1400	644	25.3	207	8.1	152	6.0	8.0	9.9	296	820	1963
1008651	P205/65R15	92	H	D	4	RSB	6.5	44	635	1400	647	25.5	214	8.4	152	6.0	8.1	10.1	298	816	1973
1012657	P205/65R15	92	H	J	4	RSB	6.0	44	635	1400	646	25.4	209	8.2	148	5.8	7.8	9.8	817	1970	
1012232	205/65R16	95	H	CK	4	RSB	6.5	44	690	1521	664	26.1	214	8.4	156	6.1	8.0	10.1	795	2025	
1009192	P205/65R16	94	H	T	4	RSB	6.5	44	670	1477	674	26.5	214	8.4	156	6.1	8.1	10.1	304	783	2054
1010865	P205/65R16	94	H	H	4	RSB	6.5	44	670	1477	666	26.2	212	8.3	156	6.1	8.1	10.3	310	792	2031
1012297	P205/65R16	94	H	U	4	RSB					665	26.2	214	8.4	156	6.1	8.4	10.6	793	2028	
1012658	P205/65R16	94	H	J	4	RSB	6.0	44	670	1477	672	26.5	209	8.2	156	6.1	7.9	9.9	785	2050	
1009084	P215/65R16	96	V	H	4	RSB	6.5	44	710	1565	682	26.9	220	8.7	166	6.5	7.8	9.7	316	774	2080
1012209	P235/65R17	103	T	H	4	RSB					736	26.2	247	8.4	176	6.9	8.8	11.1	793	2028	

OPTIMO H426- a new concept green tire-will keep our nature clean.

Technical data subject to change without prior notice. • These size are currently under development * XL : Extra Load
 * DSB : Diagonal Serrated Band * SBL : Serrated Black Letter



OPTIMO H426



M-Code	Size	LI	SR	USE	PR	S/W Type	Recom- mended Rim	Max. Air (PSI)	Max.Load		Overall Diameter		Section Width		Tread Width		Tread Depth		SLR	RPM	Rolling Circum- ference
									(kgs)	(lbs)	mm	inch	mm	inch	mm	inch	mm	inch (32")			

60

1012823	175/60R14	79	H	J	4	RSB	5.0	44	437	963	566	22.3	177	7.0	130	5.1	7.4	9.3	932	1726	
1011286	P185/60R14	82	H	-	4	RSB	5.5	44	475	1047	578	22.8	186	7.3	179	7.0	7.6	9.5	913	1763	
1011287	P195/60R14	85	H	-	4	RSB	6.0	44	515	1135	588	23.1	205	8.1	160	6.3	8.1	10.2	897	1793	
1012664	175/60R15	81	H	J	4	RSB	5.0	44	462	1019	591	23.3	177	7.0	130	5.1	7.4	9.3	893	1803	
1011163	185/60R15	84	H	F	4	RSB	6.0	51	500	1102	602	23.7	208	8.2	152	6.0	8.4	10.6	877	1836	
1006065	195/60R15	88	H	CH	4	RSB	6.0	44	560	1235	613	24.1	207	8.1	144	5.7	8.3	10.5	861	1870	
1012693	195/60R15	88	H	J	4	RSB	6.0	44	580	1279	640	25.2	201	7.9	144	5.7	7.7	9.7	824	1952	
1011289	P195/60R15	87	H	-	4	RSB	6.0	44	540	1190	615	24.2	201	7.9	179	7.0	7.7	9.6	858	1876	
1011290	P205/60R15	90	H	-	4	RSB	6.0	44	590	1301	627	24.7	206	8.1	179	7.0	8.0	9.9	842	1912	
1011291	P215/60R15	93	H	-	4	RSB	6.5	44	640	1411	637	25.1	228	9.0	176	6.9	8.3	10.5	828	1943	
1012645	195/60R16	89	H	-	4	RSB	6.0	44	580	1279	638	25.1	205	8.1	160	6.3	8.1	10.2	827	1946	
1012668	195/60R16	89	H	J	4	RSB	6.0	44	560	1235	615	24.2	200	7.9	160	6.3	7.6	9.5	858	1876	
1006222	215/60R16	95	V	CH	4	RSB	6.5	44	690	1521	661	26.0	226	8.9	162	6.4	8.0	10.1	798	2016	
1011298	215/60R16	95	V	-	4	RSB	6.5	44	690	1521	664	26.1	221	8.7	154	6.1	7.9	9.9	795	2025	
1010692	215/60R16	95	T	V	4	RSB					665	26.2	226	8.9	178	7.0	8.4	10.6	793	2028	
1012660	215/60R16	95	V	J	4	RSB	6.5	44	690	1521	664	26.1	221	8.7	162	6.4	7.9	9.9	795	2025	
1012486	225/60R16	98	H	-	4	RSB	6.5	44	750	1653	678	26.7	226	8.9	154	6.1	7.9	9.9	778	2068	
1006359	P205/60R16	91	H	K	4	RSB	6.5	44	615	1356	650	25.6	212	8.3	154	6.1	8.1	10.1	302	812	1981
1008652	P205/60R16	91	V	D	4	RSB	6.5	44	615	1356	652	25.7	214	8.4	154	6.1	8.1	10.1	298	809	1989
1005776	P215/60R16	94	H	R	4	RSB	7.0	44	670	1477	663	26.1	220	8.7	162	6.4	8.1	10.1	310	796	2022
1011294	P235/60R16	99	H	-	4	RSB	7.0	44	775	1709	688	27.1	239	9.4	179	7.0	8.1	10.1	767	2098	
1012669	215/60R17	96	H	J	4	RSB	6.5	44	710	1565	688	27.1	232	9.1	158	6.2	8.2	10.3	767	2099	
1012235	225/60R17	99	H	CH	4	RSB	6.5	44	775	1709	700	27.6	235	9.3	170	6.7	8.5	10.7	754	2135	
1012301	225/60R17	99	H	H	4	RSB	6.5	44	775	1709	698	27.5	235	9.3	170	6.7	8.5	10.7	329	756	2128
1013185	225/60R17	99	H	CK	4	RSB	6.5	44	775	1709	700	27.6	235	9.3	170	6.7	8.5	10.7	754	2135	
1011295	P225/60R18	99	H	-	4	RSB	6.5	44	775	1709	732	28.8	228	9.0	179	7.0	8.0	9.9	721	2233	
1012210	P235/60R18	102	H	H	4	RSB	7.0	44	850	1874	737	29.0	249	9.8	180	7.1	8.8	11.1	716	2248	

55

1007475	P195/55R15	84	V	CK	4	RSB	6.0	44	500	1102	590	23.2	212	8.3	148	5.8	8.0	10.1	894	1800	
1006708	205/55R16	90	V	C-	4	RSB	6.5	51	615	1356	626	24.6	227	8.9	172	6.8	8.2	10.3	843	1909	
1009945	205/55R16	91	H	CH	4	RSB	6.5	44	615	1356	635	25.0	219	8.6	160	6.3	8.0	10.1	831	1937	
1013069	205/55R16	91	H	CR	4	RSB	6.5	44	615	1356	635	25.0	219	8.6	160	6.3	8.0	10.1	831	1937	
1011283	215/55R16	XL 97	-	-	4	RSB	7.0	50	730	1609	638	25.1	231	9.1	171	6.7	8.0	10.1	827	1947	
1011284	225/55R16	95	H	-	4	RSB	7.0	51	690	1521	654	25.7	231	9.1	179	7.0	7.8	9.7	807	1995	
1012353	P195/55R16	86	T	K	4	RSB	6.0	44	530	1168	620	24.4	201	7.9	179	7.0	7.8	9.8	292	894	1891
1005369	P205/55R16	89	H	H	4	RSB	6.0	44	580	1279	637	25.1	205	8.1	160	6.3	7.8	9.7	298	828	1943
1010012	P205/55R16	89	H	T	4	RSB	6.0	44	580	1279	636	25.0	205	8.1	160	6.3	7.8	9.7	298	830	1940
1010200	P205/55R16	89	H	I	4	RSB	6.5	44	580	1279	636	25.1	211.4	8.3	160	6.3	7.8	9.7	299	829	1941
1010210	P205/55R16	89	H	U	4	RSB	6.5	44	580	1279	633	24.9	212.6	8.4	160	6.3	7.8	9.7	297	833	1933
1010582	P205/55R16	89	H	X	4	RSB	6.5	44	580	1279	633	24.9	214	8.4	164	6.5	7.8	9.8	298	834	1931
1011352	P205/55R16	89	H	Y	4	RSB	6.5	44	580	1279	633	24.9	214	8.4	164	6.5	7.8	9.8	298	834	1931
1012432	P205/55R16	89	H	P	4	RSB	6.5	44	580	1279	634	25.0	213	8.4	160	6.3	6.8	8.6	297	832	1934
1012454	P205/55R16	89	H	O	4	RSB	6.5	44	580	1279	634	25.0	214	8.4	160	6.3	7.8	9.8	297	832	1934
1012773	P205/55R16	89	H	J	4	RSB					629	24.8	230	9.1	168	6.6	8.0	10.1	839	1919	
1010383	215/55R17	94	H	V	4	RSB	8.0	51	670	1477	672	26.5	227	8.9	180	7.1	8.1	10.1	310	785	2050
1012233	215/55R17	94	V	CK	4	RSB	6.5	44	670	1477	665	26.2	235	9.3	170	6.7	8.0	10.1	793	2028	
1011302	235/55R17	99	H	-	4	RSB	7.5	51	775	1709	690	27.2	243	9.6	187	7.4	7.8	9.7	765	2105	
1007623	P215/55R17	93	V	T	4	RSB	6.5	44	650	1433	664	26.1	213	8.4	186	7.3	7.8	9.7	308	795	2025
1009002	P215/55R17	93	V	U	4	RSB	7.0	44	650	1433	670	26.4	224	8.8	166	6.5	7.6	9.5	302	788	2044
1007159	P225/55R17	95	H	H	4	RSB	6.5	44	690	1521	684	26.9	225	8.9	186	7.3	7.8	9.7	318	771	2086
1009085	P225/55R17	95	V	H	4	RSB	7.0	44	690	1521	681	26.8	231	9.1	166	6.5	7.8	9.7	316	775	2077
1005483	P235/55R17	98	V	H	4	RSB	7.0	44	750	1653	690	27.2	240	9.4	160	6.3	7.8	9.7	319	765	2105
1012196	P235/55R17	98	V	I	4	RSB					684	26.9	252	9.9	176	6.9	8.0	10.1	771	2086	
1012302	225/55R18	98	H	H	4	RSB	6.5	44	750	1653	701	27.6	225	8.9	170	6.7	8.0	10.0	332	753	2138
1012784	225/55R18	98	H	R	4	RSB					699	27.5	238	9.4	170	6.7	8.5	10.7	755	2132	
1012356	235/55R18	100	H	T	4	RSB	7.0	44	800	1764	710	28.0	237	9.3	187	7.4	8.2	10.3	336	743	2166
1011285	P225/55R18	97	H	-	4	RSB	7.0	44	730	1609	705	27.8	231	9.1	179	7.0	7.8	9.7	748	2150	
1012211	P235/55R19	101	H	H	4	RSB	7.5	44	825	1819	738	29.1	257	10.1	184	7.2	8.5	10.7	715	2251	

OPTIMO H426- a new concept green tire-will keep our nature clean.

Technical data subject to change without prior notice. • These size are currently under development * XL : Extra Load
* DSB : Diagonal Serrated Band * SBL : Serrated Black Letter



OPTIMO H426



M-Code	Size	LI	SR	USE	PR	S/W Type	Recom- mended Rim	Max. Air (PSI)	Max.Load		Overall Diameter		Section Width		Tread Width		Tread Depth		SLR	RPM	Rolling Circum- ference
									(kgs)	(lbs)	mm	inch	mm	inch	mm	inch	mm	inch (32")			

50

1011165	195/50R16	84	H	F	4	RSB	6.5	51	500	1102	602	23.7	207	8.1	174	6.9	8.1	10.2	876	1836	
1011740	195/50R16	84	H	CK	4	RSB	6.0	44	500	1102	597	23.5	214	8.4	150	5.9	8.0	10.1	884	1821	
1006066	205/50R16	87	V	CH	4	RSB	6.5	44	545	1201	608	23.9	222	8.7	160	6.3	8.3	10.5	868	1854	
1011282	225/50R16	92	V	-	4	RSB	7.0	51	630	1389	632	24.9	229	9.0	179	7.0	7.8	9.7	835	1928	
1011281	P205/50R16	86	H	-	4	RSB	6.5	44	530	1168	612	24.1	212	8.3	164	6.5	7.8	9.7	862	1867	
1012646	215/50R17	XL 95	-	-	4	RSB	7.0	50	690	1521	648	25.5	224	8.8	171	6.7	7.8	9.8	814	1976	
1011301	225/50R17	94	V	-	4	RSB	7.0	51	670	1477	657	25.9	231	9.1	179	7.0	7.8	9.7	803	2004	
1008653	P215/50R17	90	H	D	4	RSB	7.0	44	615	1356	648	25.5	226	8.9	154	6.1	7.7	9.6	300	814	1976
1011300	P215/50R17	XL 93	-	-	4	RSB	7.0	50	650	1433	648	25.5	224	8.8	171	6.7	7.8	9.8	814	1976	
1006084	P225/50R17	93	H	K	4	RSB	6.5	50	615	1356	657	25.9	224	8.8	182	7.2	8.1	10.1	304	803	2004
1010878	P225/50R17	93	H	T	4	RSB	6.5	44	650	1433	657	25.9	224	8.8	174	6.9	8.1	10.1	305	803	2004
1012482	P245/50R17	98	V	-	4	RSB	7.5	44	750	1653	678	26.7	249	9.8	196	7.7	7.8	9.7	778	2068	
1006906	P235/50R18	97	V	H	4	RSB	7.5	44	730	1609	689	27.1	243	9.6	186	7.3	7.8	9.7	322	766	2101
1010055	P235/50R18	97	V	I	4	RSB	7.5	44	730	1609	690	27.2	242	9.5	186	7.3	7.8	9.7	322	765	2105
1012307	P235/50R18	97	V	T	4	RSB					684	26.9	254	10.0	186	7.3	8.0	10.1	771	2086	
1005484	P245/50R18	99	V	H	4	RSB	7.5	44	775	1709	699	27.5	251	9.9	160	6.3	7.8	9.7	325	755	2132
1012197	P245/50R18	99	V	I	4	RSB	7.5	44	775	1709	687	27.0	270	10.6	194	7.6	8.0	10.1	768	2095	
1010579	P235/50R19	99	H	G	4	RSB					718	28.3	245	9.6	205	8.1	8.4	10.6	735	2190	
1010505	P255/50R20	104	H	F	4	RSB	8.5	51	900	1984	767	30.2	271	10.7	148	5.8	8.5	10.7	688	2339	

45

1012111	205/45R17	84	V	K	4	RSB	6.5	44	500	1102	618	24.3	199	7.8	168	6.6	7.8	9.8	292	854	1885
1013374	205/45R17	84	V	T	4	RSB	6.5	44	500	1102	618	24.3	199	7.8	168	6.6	7.8	9.8	292	854	1885
1005930	215/45R17	XL 91	H	-	4	RSB	7.0	50	615	1356	626	24.6	210	8.3	182	7.2	7.7	9.6	295	843	1909
1012345	215/45R17	XL 91	C-	-	4	RSB	7.0	50	615	1356	620	24.4	222	8.7	182	7.2	8.2	10.3	851	1891	
1011365	P215/45R17	87	H	T	4	RSB	7.0	44	545	1201	629	24.8	214	8.4	180	7.1	7.8	9.8	298	839	1918
1012483	P215/45R17	87	H	X	4	RSB	7.0	44	545	1201	628	24.7	221	8.7	180	7.1	8.0	10.1	298	840	1915
1010454	225/45R18	91	V	CK	4	RSB	7.0	44	615	1356	654	25.7	233	9.2	180	7.1	8.2	10.3	807	1995	
1012980	225/45R18	XL 95	CM	-	4	RSB	7.5	50	690	1521	654	25.7	233	9.2	180	7.1	8.2	10.3	807	1995	
1010384	235/45R18	94	H	V	4	RSB	8.0	51	670	1477	672	26.5	239	9.4	190	7.5	8.1	10.3	317	785	2050
1010201	P225/45R18	91	V	I	4	RSB	7.0	44	615	1356	656	25.8	218	8.6	180	7.1	8.0	9.9	310	805	2000
1010211	P225/45R18	91	V	T	4	RSB	7.0	44	615	1356	655	25.8	218	8.6	180	7.1	8.0	9.9	311	805	1998
1012434	P235/45R18	94	V	K	4	RSB	7.5	44	670	1477	667	26.3	243	9.6	190	7.5	8.2	10.3	316	791	2035
1012102	P245/45R18	96	V	V	4	RSB	7.5	44	710	1565	672	26.5	258	10.2	200	7.9	8.4	10.6	785	2050	
1011261	P245/45R19	98	V	H	4	RSB	8.0	44	750	1653	703	27.7	249	9.8	174	6.9	7.8	9.7	326	751	2144
1010072	P245/45R19	98	W	I	4	RSB					691	27.2	258	10.2	196	7.7	8.0	10.1	764	2108	
1010281	255/45R20	101	V	F	4	RSB	8.0	51	825	1819	738	29.1	255	10.0	148	5.8	8.5	10.7	337	715	2251

40

1012455	215/40R18	85	V	K	4	SBL	7.5	44	515	1135	628	24.7	231	9.1	180	7.1	8.4	10.6	840	1915	
1011428	225/40R18	XL 92	H	-	4	RSB	8.0	50	630	1389	633	24.9	240	9.4	180	7.1	8.0	10.1	834	1931	
1012701	P245/40R19	94	V	K	4	RSB	8.0	44	670	1477	673	26.5	263	10.4	208	8.2	8.4	10.6	784	2053	
1011262	P275/40R19	101	V	H	4	RSB	9.0	44	825	1819	703	27.7	273	10.7	174	6.9	7.8	9.7	326	751	2144
1010073	P275/40R19	101	W	I	4	RSB					689	27.1	292	11.5	220	8.7	8.0	10.1	766	2102	

Technical data subject to change without prior notice. • These size are currently under development * XL : Extra Load
 * DSB : Diagonal Serrated Band * SBL : Serrated Black Letter

OPTIMO H426- a new concept green tire-will keep our nature clean.