



Vantra LT



M-Code	Size	USE	PR	S/W Type	Recom- mended Rim	Max. Air (PSI)		Max. Load				Overall Diameter		Section Width		Tread Width		Tread Depth		RPM	Rolling Circum- ference
						S	D	(kgs)		(lbs)		mm	inch	mm	inch	mm	inch	mm	inch (32")		
								S	D	S	D										

75

2001972	• 185/75R14 102/100	E-	8	DSB	5.0	70	70	850	8800	1875	1765	631	24.8	184	7.2	138	5.4	9.0	11.3	836	1925
2001951	• 205/75R14 109/107 R	-	8	DSB	6.0	70	70	1030	975	2770	2150	661	26.0	202	8.0	156	6.1	10.0	12.6	798	2016
2001970	• 175/75R16 101/99	E-	8	DSB	5.0	70	70	825	775	1820	1710	666	26.2	178	7.0	130	5.1	9.0	11.3	792	2031
2001944	• 195/75R16 110/108 R	-	10	DSB	5.5	80	80	1060	1000	2335	2205	697	27.4	196	7.7	148	5.8	10.0	12.6	757	2125
2001987	• 205/75R16 113/111	E-	10	DSB	5.5	80	80	1150	1090	2535	2405	713	28.1	154	6.1	156	6.1	10.0	12.6	740	2174
2001957	• 215/75R16 116/114 R	-	10	DSB	6.0	80	80	1250	1180	2755	2600	740	29.1	219	8.6	172	6.8	10.0	12.6	713	2256
2001998	• 225/75R16 121/120	E-	10	DSB	6.0	85	85	1450	1400	3195	3085	740	29.1	219	8.6	172	6.8	10.0	12.6	713	2256

70

2001979	• 195/70R15 100/98	E-	6	DSB	6.0	55	55	800	750	1765	1655	654	25.7	202	8.0	144	5.7	10.0	12.6	807	1994
2001941	• 195/70R15 104/102 R	-	8	DSB	6.0	65	65	900	850	1985	1875	654	25.7	202	8.0	144	5.7	10.0	12.6	807	1994
2001950	• 205/70R15 106/104 R	-	8	DSB	6.0	65	65	950	900	2095	1985	667	26.3	211	8.3	152	6.0	10.0	12.6	791	2034
2001985	• 205/70R15 106/104	E-	8	DSB	6.0	65	65	950	900	2095	1985	667	26.3	211	8.3	152	6.0	10.0	12.6	791	2034
2001954	• 215/70R15 109/107 S	-	8	DSB	6.5	65	65	1030	975	2270	2150	681	26.8	218	8.6	164	6.5	10.0	12.6	775	2076
2001992	• 215/70R15 109/107	E-	8	DSB	6.5	65	65	1030	975	2270	2150	681	26.8	218	8.6	164	6.5	10.0	12.6	775	2076

65

2001982	• 205/65R15 102/100	E-	6	DSB	6.0	55	55	850	800	1875	1765	643	25.3	216	8.5	156	6.1	9.5	12.0	821	1961
2001976	• 195/65R16 104/102	E-	8	DSB	6.0	70	70	900	850	1985	1875	658	25.9	208	8.2	148	5.8	9.5	12.0	802	2008
2001983	• 205/65R16 107/105	E-	8	DSB	6.0	70	70	975	925	2150	2040	668	26.3	216	8.5	160	6.3	9.5	12.0	790	2038
2001990	• 215/65R16 109/107	E-	8	DSB	6.5	70	70	1030	975	2270	2150	684	26.9	226	8.9	168	6.6	9.5	12.0	771	2087
2001999	• 235/65R16 115/113	E-	8	DSB	7.0	70	70	1215	1150	2680	2535	715	28.1	240	9.4	184	7.2	9.2	11.6	738	2181

2001966	• 155R12 88/86 P	E	8	DSB	4.5	65	65	560	530	1235	1170	548	21.6	155	6.1	112	4.4	8.5	10.7	963	1671
2001964	• 165R14 97/95 Q	E	8	DSB	4.5	65	65	730	690	1610	1520	619	24.4	165	6.5	120	4.7	9.0	11.3	852	1889
2001971	• 175R14 99/98	E-	8	DSB	5.0	65	65	775	750	1710	1655	630	24.8	176	6.9	126	5.0	9.0	11.3	837	1923
2001939	• 185R14 102/100 R	-	8	DSB	5.5	65	65	850	800	1875	1765	648	25.5	184	7.2	134	5.3	9.0	11.3	814	1978
2001974	• 185R14 102/100	E-	8	DSB	5.5	65	65	850	850	1875	1765	648	25.5	184	7.2	134	5.3	9.0	11.3	814	1978
2001981	• 195R14 106/104	E-	8	DSB	5.5	65	65	950	900	2095	1985	663	26.1	194	7.6	140	5.5	10.0	12.6	795	2023
2001988	• 205R14 109/107	E-	8	DSB	6.0	65	65	1030	975	2270	2150	683	26.9	203	8.0	152	6.0	10.0	12.6	772	2084
2001995	• 215R14 112/110	E-	8	DSB	6.0	65	65	1120	1060	2470	2335	698	27.5	214	8.4	160	6.3	10.0	12.6	755	2130
2002000	• 185R15 103/102	E-	8	DSB	5.5	65	65	875	850	1930	1875	673	26.5	184	7.2	134	5.3	9.0	11.3	784	2052

Technical data subject to change without prior notice. • These sizes are currently under development.
 * XL : Extra Load * DSB : Diagonal Serrated Band * OWL : Outlined White Letter

Exceptionally Durable Summer Tyre with Improved Mileage for Commercial Van and Transporters.