

LUTEC  PRODUCT INFORMATION SHEET		
Public information	Supplier's name or trade mark	LUTEC
	Supplier's address	LUTEC Europe NV,Herentalsebaan 425. B-2160 Wommelgem-Belgium
	Model Identifier - Luminaire Supplier	6501702330
	Light sources maker model	6501702330M
	Date of first placing on the market	2021/10/15
	Date of end of placement on the market	
	Compliance data visible to UK MSA	yes
TYPE OF LIGHT SOURCE	Lighting technology used	LED
	Non-directional or directional	NDLS
	Light source cap-type (or other electric interface)	terminal blocks
	Mains or non-mains	Non-mains
	Connected light source (CLS)	yes
	Colour-tuneable light source	yes
	High luminance light source	no
	Anti-glare shield	no
	Dimmable	yes
GENERAL PRODUCT PARAMETERS	Energy consumption in on-mode (KWh/1000h)	4
	Energy efficiency class	G
	Useful luminous flux (lm)	220
	Beam angle correspondence	Spere(360°)
	Correlated colour temperature type	Range
	Correlated colour temperature (K)	2700-6500
	On-mode power (W)	3.3
	Standby power (W)	≤0.5W
	Networked standby power for CLS (W)	≤0.5W
	Colour rendering index	80
	Colour rendering index range (Minimum)	80
	Colour rendering index range (Maximum)	80
	Outer dimensions (Height) (millimetre)	10
	Outer dimensions (Width) (millimetre)	112
	Outer dimensions (Depth) (millimetre)	90
	Claim of equivalent power	no
	Equivalent power (W)	/
	Chromaticity coordinate (x)	0.463
	Chromaticity coordinate (y)	0.42
Directional light source	Peak luminous intensity (cd)	
	Beam angle (degrees)	
	Beam angle range (Minimum) (degrees)	
	Beam angle range (Maximum) (degrees)	
File upload	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
PARAMETERS FOR LED AND OLED LIGHT SOURCES	R9 Color rendering index	9
	Survival factor	1
	Lumen maintenance factor	0.96
PARAMETERS FOR LED AND OLED MAINS LIGHT SOURCES	Displacement factor	/
	Color consistency in McAdam ellipses	/
	Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage	/
	Flicker metric(W)	/
	Stroboscopic effect metric(W)	/