## **Product Information Sheet**

without

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or  | trade mark: LUTEC                                       |
|---------------------|---|
| Supplier's address: | LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem, BE |

| Model identifie  | r: 5188801118M |                           |  |              |
|--|----------------|---------------------------|--|--------------|
| Type of light so   | urce:          |                           |  |              |
| Lighting technology used:  |                | LED                       | Non-directional or directional:  | NDLS         |
| Light source cap-type  |                | Welding                   |  |              |
| (or other electric interface)  |                |                           |  |              |
| Mains or non-mains:  |                | MLS                       | Connected light source (CLS):  | No           |
| Colour-tuneable light source:  |                | No                        | Envelope:  | -            |
| High luminance light source:   |                | No                        |  |              |
| Anti-glare shield:   |                | No                        | Dimmable:  | No           |
|  |                | Product parar             | neters   |              |
| Parameter  |                | Value                     | Parameter  | Value        |
|  |                | General product p         | arameters:   |              |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                | 14                        | Energy efficiency class  | E            |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                | 1 550 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000        |
| On-mode power (P <sub>on</sub> ), expressed in W   |                | 14,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80           |
| Outer  | Height         | 15                        | Spectral power   | See image    |
| dimensions   | Width          | 128                       | distribution in the  | in last page |

143

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)                      |      | range 250 nm to 800<br>nm, at full-load |              |  |  |  |
|---|------|---|--------------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>  | Yes  | If yes, equivalent power (W)            | 102          |  |  |  |
|   |      | Chromaticity                            | 0,440        |  |  |  |
|   |      | coordinates (x and y)                   | 0,403        |  |  |  |
| Parameters for LED and OLED light sources:  |      |   |              |  |  |  |
| R9 colour rendering index value   | 8    | Survival factor                         | 1,00         |  |  |  |
| the lumen maintenance factor  | 0,96 |   |              |  |  |  |
| Parameters for LED and OLED mains light sources:  |      |   |              |  |  |  |
| displacement factor (cos φ1)  | 0,70 | Colour consistency in McAdam ellipses   | 6            |  |  |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W)       | <del>-</del> |  |  |  |
| Flicker metric (Pst LM)   | 1,0  | Stroboscopic effect metric (SVM)        | 1,0          |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

