



Tork Premium Cloth 510 Roll



artikel: 510104

stelsysteem: W1 - Poetsdoeken
muur/vloer/standaard systeem

Lagen: 1

Kleur: Wit

Print: nee

Reliëf:

Rollbreedte: 42.8 cm

Rollengte: 380 m

Aantal vellen: 1000

producteigenschappen

- Extra zacht
- Pluisarm
- Groot absorptie vermogen
- Komt gemakkelijk in kleine hoekjes en gaatjes

verzendinggegevens

consumenteneenheid:

EAN: 7322540057256

stuks: 1

hoogte: 437 mm

breedte: 391 mm

lengte: 391 mm

volume: 66.81 dm³

nettogewicht: 8945 g

brutogewicht: 9747 g

transportunit:

EAN: 7322540057256

stuks: 1

consumenteneenheden: 1

materiaal: Carton

hoogte: 437 mm

breedte: 391 mm

lengte: 391 mm

volume: 66.81 dm³

nettogewicht: 8.95 kg

brutogewicht: 9.75 kg

milieu

Content

Chemical pulp, Polypropene, Polyester, Chemicals

Material



Chemical pulpChemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities. There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free). ECF is based on oxygen, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone. ECF is used in this product.

PolypropenePolypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length. PolyesterPolyester fibre is produced from terephthalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length. Chemicals Both functional and process chemicals are used. The functional chemical used is wet strength agent. The wet strength agent is a polyamide (from polyamide/epichlorhydrine polymer) with a very high affinity to the fibre. Process chemical used is a surfactant.

Production

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destroyed. The product itself is suitable for incineration. Contact local authorities before destruction.