



E400 - PVC Tape Premium

Description	Soepel blijvende vinylfilm voorzien van een hoogwaardige rubber kleeflaag.
Product properties	<ul style="list-style-type: none">* Blijft zeer soepel bij lage temperaturen* Gemakkelijk te verwerken* Hoge mechanische sterkte* Tape herstelt zich na uitrekken en kan daardoor strak gewikkeld worden* Goed weersbestendig* Vergaand bestand tegen zuren,logen, olie,
Applications	<ul style="list-style-type: none">* Wikkelen van buizen om corrosie te voorkomen* Maskeren tijdens galvanoprocessen* Afdichtingstape voor spiraalkanalen en isolatieplaten
Storage and ageing	De condities waaronder het product wordt opgeslagen, beïnvloedt zijn specificaties. Opslag dient in originele verpakking te geschieden, bij een temperatuur van 21°C (70°F) en een relatieve vochtigheid van 50%, en uit het directe zonlicht.
Applying tips	Voor de optimale hechting adviseren wij om de tape onder druk aan te brengen op een droge, stofvrije en ontvette ondergrond, die ongeveer dezelfde temperatuur heeft als de tape.
Additional technical properties	kleuren: zwart, wit, grijs en geel.
Tolerance	Tolerantie dikte total: +/- 0,03mm

TECHNICAL DATA

Carrier	PVC/film	
Adhesive	Rubber	
Thickness Total	0,2 mm	7,87 Mils
Adhesion on stainless steel	1,25 N/25mm	0,286 Lbs/inch
Tensile strength length	37 N/25mm	8,45 Lbs/inch
Elongation length	100 %	
Dielectric strength	8 kV	

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes Benelux B.V.
Van Hennaertweg 10
2952 CA Alblasserdam
tel +31 (0)78 699 21 00
fax +31 (0)78 699 21 99
www.stokvistapes.nl
info@stokvistapes.nl