



HDT-50 is an aluminium foil tape special developed for the H&V industry; good adhesion and conformance; for superior vapour sealing of Fiberglas ductboard



excellent moisture barrier

high initial tack

economical !

easy to use

exceptional performance

For further information or special applications contact manufacturer :

Carlisle Hardcast europe b.v.
Bloemendalerweg 25 – 33
P.O. Box 299,
1380 AG Weesp
The Netherlands

phone (0)294-414155
fax (0)294-418655
E-mail hardcast@xs4all.nl

Description: a high strength aluminium foil alloy tape with an unique high tack adhesive; developed for the H&V industry as a sealing tape for fibre glass duct board systems or insulation

Construction: a dead soft aluminium foil coated with a long lasting, UV resistant adhesive on one side and lined with a release paper to protect the adhesive face

Application: designed specifically for sealing prefabricated aluminium foil faced glass duct systems; also suitable for heat/light reflection, screening on electronic equipment, sealing cold store insulation, packing refrigerated export containers and decoration.

Sizes: all rolls 50meter length; standard width 50mm, 75mm and 100mm

Packing:
50mm - 24 rolls/carton
75mm - 16 rolls/carton
100mm - 12 rolls/carton

Omschrijving : een sterke, hoogwaardige aluminium tape met een bijzondere hoge initiele kleeftkracht; speciaal ontwikkeld voor de verwarming en ventilatie industrie voor het afplakken van aluminium gelamineerde oppervlakken en isolatie.

Samenstelling : een 30micron aluminum folie aan 1 zijde voorzien van een UV bestendige acrylaat kleeftlaag en afgeschermd met een papieren gesiliconeerde schutlaag

Toepassing : speciaal ontwikkeld voor hechting op aluminium gelamineerde glaswoldekens; ook geschikt als warmte/licht reflectie, afscherming, isolatie, verpakking of decoratie middel

Afmetingen : rollen 50meter lengte; standaard breedte 50mm, 75mm en 100mm

Verpakking :
50mm - 24 rol/doos
75mm - 16 rol/doos
100mm - 12 rol/doos

Technical data / Technische gegevens :

<i>thickness alu</i>	: 0.030mm
<i>tensile strength</i>	: 3,9kg/cm
<i>adhesive</i>	: UV resistant acrylic
<i>liner</i>	: release paper
<i>adhesion to steel</i>	: 0,6kg/cm (after 1hour) 0,9kg/cm (after 24hours)
<i>moisture vap. perm.</i>	: <1gr./m2 / 24hrs / 38°C / 90%RH
<i>application temperat.</i>	: +5°C / +60°C (can be applied at temp. down to 0°C as long as surface is free from ice or moisture)
<i>temperture.range</i>	: -40°C / +120°C
<i>shelflife/storage</i>	: max.2 years, dry, in closed packing (between 5°-35°C)

Each product of Carlisle Hardcast Europe b.v. is warranted to be suitable for the specialised application for which it is intended. Since the methods and conditions of application are vital factors in the satisfactory performance of such products, and such factors are beyond our control, our warranty is limited to the refund of a specific product found by our company to be defective. The products of Carlisle Hardcast Europe b.v. are designed to serve such a wide variety of specialised applications that it is not practical include instructions for all uses. Special information furnished on request.