



AXK

Diametro albero (mm) <i>Shaft diameter (mm)</i>	Sigla <i>Designation</i>	Peso (g) <i>Weight (g)</i>	Dimensioni (mm) <i>Dimensions (mm)</i>			Coefficienti di carico (N) <i>Basic load ratings (N)</i>		Velocità limite <i>Limiting Speed</i>
			Dc1	Dc	Dw	Dinamico C <i>Dynamic C</i>	Statico C ₀ <i>Static C₀</i>	
4	AXK 0414 TN	0.7	4	14	2	4 380	7 500	20 000
5	AXK 0515 TN	0.8	5	15	2	4 680	9 100	20 000
6	AXK 0619 TN	1	6	19	2	6 740	15 400	18 000
8	AXK 0821 TN	2	8	21	2	7 750	19 000	17 000
10	AXK 1024	3	10	24	2	9 150	24 500	16 000
12	AXK 1226	3	12	26	2	9 860	28 600	14 250
15	AXK 1528	4	15	28	2	11 200	35 500	12 350
17	AXK 1730	4	17	30	2	11 800	38 600	11 400
20	AXK 2035	5	20	35	2	12 900	45 600	9 500
25	AXK 2542	7	25	42	2	13 800	57 800	8 000
30	AXK 3047	8	30	47	2	15 600	69 500	6 500
35	AXK 3552	10	35	52	2	16 900	80 100	6 100
40	AXK 4060	16	40	60	3	27 500	113 500	5 700
45	AXK 4565	18	45	65	3	29 050	127 600	4 750
50	AXK 5070	20	50	70	3	31 500	138 500	4 500
55	AXK 5578	28	55	78	3	37 400	185 000	4 100
60	AXK 6085	33	60	85	3	43 900	232 500	3 800
65	AXK 6590	35	65	90	3	45 800	254 600	3 500
70	AXK 7095	60	70	95	4	53 600	254 600	3 300
75	AXK 75100	61	75	100	4	54 500	264 500	3 100
80	AXK 80105	63	80	105	4	55 600	278 500	2 900
85	AXK 85110	67	85	110	4	57 500	275 000	2 850
90	AXK 90120	86	90	120	4	72 500	401 000	2 500
100	AXK 100135	104	100	135	4	90 500	559 500	2 400
110	AXK 110145	122	110	145	4	96 500	617 500	2 200
120	AXK 120155	131	120	155	4	101 500	679 000	2 000
130	AXK 130170	205	130	170	5	132 400	838 900	1 800
140	AXK 140180	219	140	180	5	137 200	899 000	1 700
150	AXK 150190	232	150	190	5	142 800	959 000	1 600
160	AXK 160200	246	160	200	5	147 600	1 015 000	1 500

TN= Gabbia in materiale plastico, temperatura di funzionamento ammessa: 80°C (continuativi).
 TN= Plastic cage; temperature allowed: 80°C. (continuous working).

Lubrificazione con grasso: 25% in meno dei valori indicati in tabella.
 Grease lubrication: less 25% of value indicated in tables.