



■ **Insulated receptacles 0.5 - 6 mm²**

- For fine and superfine stranded conductors

Characteristics

- With solid dielectric insulation
- Insulation sleeve: PVC / PA, free of halide
- Colour-coding for cross-section assignment

Material

- CuZn (brass)

Surface

- tin plated

Nominal cross section mm ²	Part No.	Colour	Tab Thickn.	Tab Width	Dimension mm			Insulation material	Weight/ 100 pcs. ~ kg	pcs.
					l1	l2	s			
0.5-1	8201V	■	0.5	2.8	19.0	5.5	0.25	PA	0.07	100
	8201AV	■	0.8	2.8	19.0	5.5	0.25	PA	0.07	100
	8202V	■	0.5	4.8	20.0	7.0	0.30	PVC	0.10	100
	8203V	■	0.8	4.8	20.0	7.0	0.30	PVC	0.10	100
	720V	■	0.8	6.3	21.0	7.5	0.45	PVC	0.08	100
1.5-2.5	8301V	■	0.5	2.8	20.0	8.0	0.35	PVC	0.14	100
	8301AV	■	0.8	2.8	20.0	8.0	0.35	PVC	0.14	100
	8302V	■	0.5	4.8	20.5	7.0	0.30	PVC	0.11	100
	8303V	■	0.8	4.8	20.5	7.0	0.30	PVC	0.11	100
	730V	■	0.8	6.3	21.0	7.5	0.45	PVC	0.15	100
4-6	8502V	■	0.5	4.8	20.5	9.5	0.40	PVC	0.15	100
	8503V	■	0.8	4.8	20.5	9.5	0.40	PVC	0.15	100
	750V	■	0.8	6.3	25.5	11.5	0.45	PVC	0.16	100

► Tool: see chart page 184