



**Mark 3013 hand-hydraulisch
met opklapbaar buigframe**

Specificaties

Max. persdruk pomp	130kN (13.000 kg)
Motorvermogen	
Gewicht inclusief standaarduitrusting en buigmallen (kg)	182
Afmeting transportkist (cm)	118 × 43 × 50

Gas- en stoompijp

Standaardbuigmallen bocht 90° (")	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
uitwendige diameter (mm)	17.2	21.3	26.9	33.7	42.4	48.3	60.3	76.1	88.9
Wanddikte DIN 2440 (mm)	2.35	2.65	2.65	3.25	3.25	3.25	3.65	3.65	4.05
(150 medium, ISO R65)									
Wanddikte DIN 2441 (mm)	2.9	3.25	3.25	4.05	4.05	4.05	4.50	4.50	4.85
(150 heavy, ISO R65)									
Buigradii (mm)	45	50	65	100	130	150	200	320	380
Standaarduitrusting	9 buigmallen, 2 hoekmallen met paspennen, 1 strekmal, 1 U beugel en 1 verlengplunjer								

Accessoires

Extra buigmallen bocht 180°	3/8	1/2	3/4	1	1 1/4	1 1/2	2
voor gas- en stoompijp (inch en mm)	17.2	21.3	26.9	33.7	42.4	48.3	60.3
Buigradii (mm)	130	130	130	130	130	140	190
Hulpapparatuur haarspeldbocht tot 180°	Toepassing mogelijk						

Vlampijp

Extra buigmallen bocht 90° (mm)	25/21	30/26	32/28	38/33	44.5/40	48.3/43.1
Buigradii (mm)	115	140	140	170	190	220
	51/46	57/51.5	60.3/54.5	63.5/57.5	70/64	76/70
	220	250	270	270	315	420

Polyetheen beklede buizen

	P21	P25	P31	P38	P46	P52	P65
Extra buigmallen bocht 90° (")	3/8	1/2	3/4	1	1 1/4	1 1/2	2

Buigradii (mm)	110	110	137	140	170	220	270	
Constructiepijp								
Extra buigmallen bocht 90° (")	1/2		3/4		1		1 1/4	
Uitwendige diam./materiaal-dikte (mm)	21.3×1.75		26.9×1.75		33.7×2.00		42.4×2.00	
Buigradii (mm)	110		137		190		220	
Platijzer 8 × 40 mm								
Extra buigmallen bocht tot 180°	120	140	160	180	200	220	240	260
binnendiameter (mm)								
Buigapparatuur bochten t/m 180°	Toepassing mogelijk							
Draaibare driepoot	Toepassing mogelijk							