




Push-in fittings QSM, Quick Star, mini

Technical data

Push-in fitting QSM

Male thread
with external hex



Dimensions and ordering data												
Connection	Nominal size	Tubing O.D.	D5 Ø	L1	L2	L3	L4	⌀	Weight/ piece [g]	Part No.	Type	PU*
D1	[mm]	D2										
Metric thread with sealing ring												
M3	0.9	2	4.8	12.1	2.5	–	8.4	5	1	133027	QSM-M3-2	10
		3	7	13.3	2.5	–	9.6	5.5	1.1	153301	QSM-M3-3	10
										130775	QSM-M3-3-100	100
	1.1	4	9.8	15.7	2.5	–	11.5	8	2.4	153303	QSM-M3-4	10
										130776	QSM-M3-4-100	100
M5	1.1	2	4.8	11.8	3	–	8.4	7	2.2	133028	QSM-M5-2	10
	2	3	9.8	16.2	3	–	11.5	8	3.4	153302	QSM-M5-3	10
										130777	QSM-M5-3-100	100
	2.2	4	9.8	16.2	3	–	11.5	8	3.2	153304	QSM-M5-4	10
										130778	QSM-M5-4-100	100
	2.1	6	11.8	17.3	3	–	12	10	4.5	153306	QSM-M5-6	10
										130779	QSM-M5-6-100	100
M6	2.8	6	11.8	18	3.9	–	11.7	10	4.8	132600	QSM-M6-6	1
R thread												
R 1/8	2.9	4	–	16	8	12	11.5	10	6	153305	QSM-1/8-4	10
										130755	QSM-1/8-4-100	100
	4.5	6	–	18	8	14	12	10	6	153307	QSM-1/8-6	10
										130756	QSM-1/8-6-100	100
G thread with sealing ring												
G 1/8	2.9	4	–	16.4	5.1	–	–	13	9.4	186264	QSM-G 1/8-4	10
	2.8	6	–	18.4	5.1	–	–	13	11	186265	QSM-G 1/8-6	10

* Packaging unit quantity