

**Product Datasheet visor model 9790 048  
(with helmet bracket 9790 047 and adapter 9924 010)**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

<p><b>Produktcharacteristics</b></p>	<ul style="list-style-type: none"> <li>* Visor for helmets and with the possibility to attach earmuffs</li> <li>* Sturdy, lightweight polycarbonate visor</li> <li>* Special plug-in adapter for attachment to all standard safety helmets fitted with the necessary slot and notch</li> <li>* Visor lockable</li> <li>* Possibility of visor replacement</li> </ul>
<p><b>Technical Details</b></p> <p><b>Helmet bracket</b></p> <p>Material Colour</p> <p><b>Adaptor</b> (for combination without earmuffs)</p> <p>Colour Features</p>	<p>PA/PBT black</p> <p>black Fits to Euroslots (30 mm)</p>

<b>Lens</b>	
Material	PC
Thickness	1,4 mm
Filter	2C-1,2
Colour	clear
Optical class	1
Impact resistance	A (190 m/s)
Special markings	3, 8, 9
<b>Miscellaneous</b>	
Weight	Visor + helmet bracket: 215g Lens: 125g Helmet bracket: 90g
Standards	DIN EN 166 + DIN EN 170 main requirements and special requirements: „A“ high energy impact (→ 190 m/s) „3“ Protection against liquids (droplets or splashes) „8“ Protection against the effects fo electrical arcs (440 volts) „9“ Protection against molten metal and hot solids