



FULL FACE MASKS

Protection against gases and vapours,
mists and dusts

DATA SHEET

5150

cod. 8001035

EN 136:1998 Cl.3



EN 136:1998 performance tests		EN136	BLS 5150
Total inward leakage (%)		< 0,05	0,001
Breathing resistance (mbar)	inhal. 30 l/min	< 0,5	0,2
	inhal. 95 l/min	< 1,5	0,8
	inhal. 160 l/min	< 2,5	1,8
	exhal. 160 l/min	< 3,0	2,6
CO2 content (%)		<1,0	0,4

Main features

BLS 5150 full face mask is characterized by a soft rubber facepiece, an adjustable head harness with six fast release buckles and a panoramic visor. The inner mask is equipped with two inhalation valves, to reduce visor misting and assist comfort. The central connection for filters is threaded according to EN 148-1 standard, to be used with all the devices fitted with the same EN 148-1 male threaded connection (gas, particle and combined filters, power assisted filtering devices).

Materials

BLS 5150 full face mask is made by the following materials:

- facepiece: synthetic rubber
- inner mask: silicone
- visor: polycarbonate
- filter holder (connection): ABS
- head harness: synthetic rubber

Weight: 530 g

400 series filters

BLS 5150 full face mask can be fitted with BLS 400 series gas, particle and combined filters, equipped with standard threaded connection. The filters are fitted directly onto the central connection of the mask. BLS 5150 full face mask is also fitted as component of the BLS power assisted filtering devices SGE 2600 model.

Correct usage

Exposure limit for full face masks with particle filters:

full face mask with filter P2 = 16 * XTLV

full face mask with filter P3 = 1000 * XTLV

Exposure limit for gas masks with filters:

full face mask + gas filter = 2000 * XTLV

Exposure limit for face masks with filters combined:

full face mask + gas filter + filter P2 = 16 * XTLV

full face mask + gas filter + filter P3 = 1000 * XTLV

* FPN (nominal protection factor) as specified in EN 529:2005

Certification

BLS 5150 full face mask fulfils the requirements of EN 136:1998 European Standard and it has the CE marking according to the European Directive 89/686/EEC, as a PPE of III category. Italcert Srl (Notified Body n°0426) is the responsible of the certification (Art. 10) and of the control (Art. 11.B). The products are manufactured in a company that is ISO 9001:2008 certified.

Certification tests

BLS 5150 full face mask meets the requirements of EN 136:1998 standard and has been submitted to the tests provided by class 3 (great resistance to radiant heat and flame - suitable for fire fighting) of the reference standard.

• Total inward leakage

The full face mask must have a good face fitting. The total inward leakage test provides that 10 subjects carry out a series of exercises simulating the work conditions fitting the respirator. During the test, the test aerosol (Sodium chloride) is measured to see how much of aerosol passes through face seal leakage and exhalation valve leakage. Total inward leakage shall be not greater than 0,05%.

• Breathing resistance

Breathing resistance offered from the mask must not be greater than the following values: during the test with breathing machine (25 cycles/min and 2,0 l/stroke) or continuous flow 160 l/min shall not exceed 2,5 mbar for inhalation and 3,0 mbar for exhalation. The inhalation resistance shall not exceed 0,5 mbar with continuous air flow 30 l/min and 1,5 mbar with continuous air flow 95 l/min.

• Carbon dioxide

The carbon dioxide content of the inhalation air (dead space) shall not exceed an average of 1,0 % (by volume).

• Resistance to radiant heat

Class 3 full face mask must be resistant to radiant heat. BLS 5150 full face mask is resistant to radial heat because it maintains the leakage after a test time of 20 minutes, also if it suffers a deformation.

• Visual field

A full face mask equipped with a visor must be designed to have a real visual field not lower than 70% (BLS 5150 = 89,3%) of the natural visual field and a binocular visual field not lower than 80% of the Natural binocular visual field (BLS 5150 = 88,1%).

Warnings

Donning and leak tightness test

After the checks necessary before use, donning the mask following the next procedure: 1) elongate the straps of the head harness as much as possible; put the harness behind the neck and put the chin into the face seal, keeping the two lower straps stretched open with the hands; 2) pull the mask over the head and adjust it on the face. Be sure that hair does not remain trapped between seal and forehead; 3) adjust the side straps, then the upper straps and finally the lower ones. Do not tight the straps excessively; 4) before entering a contaminate atmosphere, check the tightness of the mask: whilst wearing the mask, close the standard connection where the filter must be screwed using the palm of the hand and take a deep breath. The mask should collapse in towards the face and remain so for as long as you hold your breath. This check is necessary to ensure that the face seal is fitted correctly. If it is not, tighten the straps or adjust the mask over the face. Then repeat the check until the fit is perfect.

Cleaning and disinfecting

Take particular care of any contaminants deposited on the mask. All cleaning should take place in safe areas. Do not use abrasive substances to clean the visor. Cleaning and disinfection operations: 1) After removing mask and contaminated filter, clean under running water to remove most of the contaminants; then clean more fully by placing in boiling water (temperature not upper to 40°C) with a common neutral soap. If disinfection is required, use a solution of a common disinfectant based on active chlorine diluted in sodium chloride. 2) Dry the mask with a soft, clean cloth or make it dry naturally. 3) When dry, clean the visor with clean cotton wool.

Storage time: 10 years (factory sealed), as shown on label.

Storage conditions: temperature range -10°C e +50°C, Relative Humidity < 80%, as shown on label (pictogram of thermometer and umbrella)

For all the information about applications, limitations of use and maintenance, see the User's manual enclosed to each full face mask (code ISU0015_02).

Technical details

The soft thermoplastic rubber face seal offers greater user comfort.

The panoramic visor offers a distortion-free field of vision and it ensures a higher level of user safety and less vision weariness.

In order to offer a longer product lifespan and greater user safety the visor was subject to anti-fog, anti-scratch and anti-acid treatment.

The full face mask offers a greater fit guarantee and uniform seal thanks to its gasket with 6 harness joints on the rigid body of the mask and not on the soft face seal. This design avoids marking the user's face and avoids pressure points, ensuring greater user comfort and a more uniform seal to the user's face.

The valves of the inner silicone mask are completely flat and ensure a higher user safety.

The optional textile harness offers greater user comfort thanks to higher transpiring capacity and greater lightness compares to the rubber harness.

The optimal positioning of the filter grants maximum freedom of movement and does not jeopardize the field of view, offering a greater user comfort.

Optional lens frame inside the mask to insert corrective lenses.

The protective visor cover in polycarbonate material protects against impacts or the protective cover in acetate material protects against acids and solvents.

