

## A. System Overview

### B1. Cable Ties

### B2. Cable Accessories

### B3. Stainless Steel Ties

### C1. Wiring Duct

### C2. Surface Raceway

### C3. Abrasion Protection

### C4. Cable Management

### D1. Terminals

### D2. Power Connectors

### D3. Grounding Connectors

### E1. Labeling Systems

### E2. Labels

### E3. Pre-Printed & Write-On Markers

### E4. Permanent Identification

### E5. Lockout/Tagout & Safety Solutions

### F. Index

## Ball Valve Lockout Devices

- Ball valves regulating hydraulic, pneumatic, and chemical energy can be locked out quickly and easily
- Accommodates valve diameters ranging from .25 inches (6.35mm) to 3.00 inches (76.20mm)
- Constructed of rugged polypropylene providing strength, durability, and added security



| Part Number | Part Description                                                    | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|---------------------------------------------------------------------|----------------|----------------|
| PSL-BV1     | Ball valve lockout, accommodates .25" – 1.00" valve pipe diameter.  | 1              | 10             |
| PSL-BV2     | Ball valve lockout, accommodates 1.25" – 3.00" valve pipe diameter. | 1              | 10             |
| PSL-BV3     | Ball valve lockout, accommodates 2.00" – 8.00" valve pipe diameter. | 1              | 10             |
| PSL-BFV     | Butterfly valve lockout, accommodates most butterfly valve handles. | 1              | 10             |

## Multiple Lockout Device

- Device can be used alone as a lockout hasp or with provided 0.19 inches (4.8mm) diameter cable to lockout electrical disconnects, gate valves, or large cumbersome devices
- Compact and easy to install
- Constructed of rugged polycarbonate and stainless steel providing strength, durability, added security and corrosion resistance



| Part Number   | Part Description                                                                                                 | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---------------|------------------------------------------------------------------------------------------------------------------|----------------|----------------|
| PSL-MLD       | Multiple lockout device; includes lockout hasp and 6.0' (1.8m) vinyl coated galvanized steel cable with loopole. | 1              | 20             |
| PSL-MLDH-X    | Multiple lockout device (hasp only).                                                                             | 10             | —              |
| PSL-MLDC      | 6.0' (1.8m) vinyl coated galvanized steel cable with loopole (cable only).                                       | 1              | 5              |
| PSL-MLDC200   | 200.0' (61.0m) vinyl coated galvanized steel cable on roll without loopole (cable only).                         | 1              | —              |
| PSL-MLDCT     | 6.0' (1.8m) nylon coated high temperature rating galvanized steel cable with loopole (cable only).               | 1              | —              |
| PSL-MLD-CRIMP | Additional crimps for creating cable loopoles.                                                                   | 10             | 20             |
| PSL-MLD-TOOL  | Tool for installing crimps on custom-length cables using the PSL-MDLC200.                                        | 1              | 6              |



Lockout single or multiple electrical disconnects



Lockout gate valves



Immobilize large or cumbersome devices, such as forklifts

## Pneumatic Energy Lockout Device

- Pneumatic energy devices can be locked out quickly and easily without costly tool modifications or inconvenient in-line valves
- When installed on the male pneumatic fitting, prevents the ability to engage into the female fitting
- Universal compact design makes the pneumatic lockout device easy to transport and install on almost any fitting, even in tight spaces
- Rugged stainless steel construction offers superior strength, durability, added security and corrosion resistance



| Part Number | Part Description                                                                 | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|----------------------------------------------------------------------------------|----------------|----------------|
| PSL-PEL     | Pneumatic energy lockout device, 3.50" (88.9mm) diameter x 0.10" (2.54mm) thick. | 1              | 20             |