



Miniature Fuses

Ceramic Tube

T


Size
6.3 x 32 mm

Rated Voltage
250 V

Time Lag

Rated Current [A]	Part No.	Voltage Drop [mV]	Pre-arcing I ² t _s -value [A ² s]	Rated Breaking Capacity [A]	Power Dissipation [W]	Weight [kg/100]	Pack
0.050	189 100.0.050	3 000	0.035	35	0.3	0.12	100
0.063	189 100.0.063	2 500	0.06	35	0.3	0.12	100
0.080	189 100.0.080	2 000	0.13	35	0.3	0.12	100
0.100	189 100.0.100	1 500	0.17	35	0.3	0.12	100
0.125	189 100.0.125	1 200	0.26	35	0.3	0.12	100
0.160	189 100.0.160	1 100	0.44	35	0.4	0.12	100
0.200	189 100.0.200	1 000	0.84	35	0.4	0.12	100
0.250	189 100.0.250	900	1.5	35	0.5	0.12	100
0.315	189 100.0.315	800	2.4	35	0.5	0.12	100
0.400	189 100.0.400	300	0.6	35	0.2	0.12	100
0.500	189 100.0.500	300	0.9	35	0.3	0.12	100
0.630	189 100.0.630	300	1.6	35	0.3	0.12	100
0.800	189 100.0.800	250	3.5	35	0.4	0.12	100
1	189 100.1	250	4	35	0.4	0.12	100
1.25	189 100.1.25	250	5	35	0.4	0.12	100
1.6	189 100.1.6	200	10	35	0.5	0.12	100
2	189 100.2	200	16	35	0.6	0.12	100
2.5	189 100.2.5	200	24	35	0.7	0.12	100
3.15	189 100.3.15	200	42	35	0.8	0.12	100
4	189 100.4	200	70	40	1.0	0.12	100
5	189 100.5	200	130	50	1.3	0.12	100
6.3	189 100.6.3	200	230	63	1.6	0.12	100
8 ¹	189 100.8	200	370	80	2.0	0.12	100
10 ¹	189 100.10	150	630	100	2.3	0.12	100
12.5 ¹	189 100.12.5	150	820	125	2.8	0.12	100
16 ¹	189 100.16	150	1 200	160	3.0	0.12	100
20 ¹	189 100.20	150	1 600	200	4.0	0.12	100

¹ Consideration should be given to heat dissipation.



Pre-Arcing Time Limits

Rated Current	1.15 I _n	2.0 I _n	2.75 I _n	4 I _n	10 I _n
50 mA		800 ms	200 ms	80 ms	15 ms
20 A	> 1 h	30 s	6 s	2 s	300 ms

