

Product datasheet (2012-08-13)

HO stokschroeven

Toepassingen ▼

Elektrolytisch verzinkte stokschroeven met houtdraad.


Voordelen ▼

- Met torx.
- Zonder kraag.
- Exclusief plug.

Specificaties ▼

- Volgens ISO 965-2.



Type	Draad-aansluiting	Afmetingen			Sleutel-wijdte (SW)	Ø houtdraad [mm]		Code-nummer
		L. [mm]	A [mm]	B [mm]				
HO 8 x 50	M 8	50	15	30		7	100	70607
HO 8 x 80	M 8	80	40	30	6	7	100	70601
HO 8 x 120	M 8	120	50	50	8	7	100	70604
HO 10 x 120	M 10	120	50	60	8	9	100	70605
HO 12 x 120	M 12	120	40	60	9	11	100	70603
HO 8 x 100	M 8	100	40	40	6	7	100	51702
HO 8 x 140	M 8	140	50	60		7	100	51704
HO 8 x 160	M 8	160	50	50		7	100	51705
HO 10 x 60	M 10	60	20	30		9	100	51706
HO 10 x 80	M 10	80	20	50		9	100	51707
HO 10 x 100 (zonder torx)	M 10	100	30	60		9	100	51708
HO 10 x 140	M 10	140	50	60		9	100	51710
HO 10 x 160	M 10	160	40	60		9	100	51711
HO 10 x 180	M 10	180	40	60		9	100	51712
HO 12 x 100	M 12	100	35	50		9	100	51713

Wij behouden ons het recht voor om ontwerpen en technische specificaties van onze producten te wijzigen.