

|                               |                                                                                                                                                   |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>MODEL</b>                  | <b>ILC-VAC</b>                                                                                                                                    |
| <b>Product description</b>    | Single mains charger                                                                                                                              |
| <b>Input voltage</b>          | 85...264VAC, 47...63Hz                                                                                                                            |
| <b>Charging temperature</b>   | 0°C ... +40°C                                                                                                                                     |
| <b>Charge current</b>         | 800mA                                                                                                                                             |
| <b>Trickle charge current</b> | 100mA                                                                                                                                             |
| <b>Enclosure</b>              | High impact PA / Aluminium                                                                                                                        |
| <b>Weight</b>                 | 860 g                                                                                                                                             |
| <b>Dimensions</b>             | Approx. 153 mm (L) x 138 mm (W) x 88 mm (H)                                                                                                       |
| <b>Mounting</b>               | Wall mounted vertical or horizontal                                                                                                               |
| <b>Compatible product</b>     | IL-600, IL-6000 GT, IL-60, IL-80 ATEX LED, IL-800                                                                                                 |
| <b>Charging time</b>          | <b>11 h:</b> IL-60 NiMH, IL-600 NiMH, IL-6000 GT NiMH 9,0A<br><b>7 h:</b> IL-60 NiCd, IL-600 NiCd<br><b>6 h:</b> IL-80 ATEX LED NiMH, IL-800 NiMH |
| <b>Charging features</b>      | Sophisticated recharge and battery protection:<br>Charging curve control<br>Ambient temperature control                                           |
| <b>Input cable</b>            | Length 2,5 m<br>Available with Euro, UK and US socket                                                                                             |

