

Utilizing the latest infrared gas detection technology in a robust and reliable design, the Gasurveyor 700 (GS700) is a highly GASURVEYOR 700 SERIES configurable instrument with leading performance and a user-friendly interface which makes it the perfect choice for all gas utility applications.

7 Solutions *In Gas Detection*

Ensuring Compliance

Intelligent data-logging functionality together with optional GPS mapping simplifies data gathering. Our cloud based Instrument Management System (IMS) improves fleet management by providing access to field usage reports, calibration history, investigation mapping and many other bespoke reports; making it easier for our customers to demonstrate compliance.

Natural Gas Discrimination

Quickly determines the source of gas leaks, whether it's pipeline gas or naturally occurring biogas; saving valuable time and reducing detection related costs.

Flexible Configuration

The GS700 can be configured to meet specific application needs and can be customized to suit a range of user settings and languages.



Application Ready

Highly configurable to our customers' gas detection needs, providing flexibility of use without compromising on performance.


Application modes include:

- Gas leak outdoors
- Pipeline gas test
- Purge
- Search
- Barhole
- Confined space


Additional Features

- LEL & Volume Gas (infrared)
- Optional sensors including: PPM, O2, CO, H2S
- Barhole mode – configurable
- Soft-key operation
- Communication: IrDA & optional Bluetooth
- 360° Alarms
- Lightweight and rugged
- Ingress protection - IP55
- Alkaline or rechargeable battery options

The GS700 is a configurable combination instrument that fully meets the needs of gas utilities. The large display simplifies operation and allows the user to access multiple functions.





Mode options



Gas leak Outdoors

Pipeline Gas Test (PGT)

Is the gas coming from your pipeline? Avoid unnecessary excavations with this invaluable feature. Instantaneous confirmation that the gas is not from your pipeline (e.g. landfill or swamp gas). Simple user interface:



Barhole Mode

Barholing allows underground leaks to be located. The GS700 incorporates a Barhole Mode that allows compliant and consistent barholing.



TECHNICAL SPECIFICATIONS	
Size:	7.5 x 3.6 x 4.2 inches
Weight:	3.1 lbs (Alkaline) 2.9 lbs (Rechargeable)
Display:	Monochrome LCD with automatic backlighting
Temperature:	-40F to +122oF (-20oC to +50oC)
Humidity:	0 - 90% RH non-condensing
Sampling:	Integral pump with flow fail sensor; sample path is protected by a hydrophobic and cotton filter
Alarms:	360o Highly visible flashing LED Sounder ~90 dB at 0.3 m
Datalogging:	Capacity: 500 session logs Session log: user ID, date & time, gas readings, alarms, calibration/bump test data, barhole data, PGT logs Log extraction: Infrared or Bluetooth (optional) Location data via GPS (optional)
Battery:	3 x LR20 'D' size Alkaline Cells or Rechargeable Battery Pack
Battery Life:	Typically 15 hrs Alkaline, 20 hrs Rechargeable
Charge Time:	Typically 6 hrs
Construction:	Antistatic Polycarbonate ABS with conductive TPE over-moulding
Rating:	IP55 (Protected from dust & water jets)
Certification:	IECEX / ATEX II 2G (Ta = -20oC to +50oC) Ex db ia IIC T4 Gb or Ex db ia IIB T3 Gb (when fitted with a PPM gas sensor) CSA Class I Div. 1 Groups A, B, C, D T4 or Class I Div. 1 Groups C, D T3 (when fitted with a PPM gas sensor)
Warranty:	2 years