



TOOL COMPANY

55 South Main Street
Munroe Falls, OH 44262 U.S.A.

PHONE: (330) 688-6667
FAX: 800.447.4017

MATERIAL SAFETY DATA SHEET

Section I – Product Identification

CHEMICAL NAME: Cemented Carbide Product with Cobalt binder

TRADE NAME AND SYNONYMS: All Carbide Grades

CHEMICAL FAMILY: Refractory Metal Carbide

MOLECULAR WEIGHT: N/A



3 HEALTH HAZARD
0 FLAMMABILITY HAZARD
0 REACTIVITY HAZARD

NFPA 704 Identification
Information

Section II – Hazardous Ingredients

Material	CAS Number	Percent	OSHA	ACGIH
		By Weight	PEL	TLV
Tungsten Carbide (limits for Tungsten dust)	12070-12-1	80-97% *	---	5 mg/m ³
Cobalt	7440-48-4	3-20% *	0.10 mg/m ³	0.02 mg/m ³
Tantalum Carbide (limits for Tantalum dust)	12070-06-3	0-15% *	5 mg/m ³	5 mg/m ³
Vanadium Carbide (limits for Vanadium dust)	11130-21-5	0.1-2% *	0.5 mg/m ³	0.5 mg/m ³

Our carbide product contains between 3.0% and 20.0% cobalt (Chemical Abstract Service (CAS) Number 7440-48-4) which is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments of the Reauthorization Act of 1986 40 CFR 372.

* Depends on grade specifications

Section III – Physical Data

Appearance and Odor: Dark Gray Metal/No Odor

Boiling Point: N/A

Vapor Pressure (mm Hg): N/A

Vapor Density (Air = 1): N/A

Solubility in Water: Insoluble

Specific Gravity (H₂O=1): 11.0 to 15.5

Percent Volatile by Volume: 0

Evaporation Rate: N/A

How Best Monitored: Air Sample

Section IV – Health Hazard Data

Grinding cemented carbide product will produce dust of potentially hazardous ingredients that can be inhaled, swallowed or come in contact with the skin or eyes.

Primary Routes of Exposure	Effects of Overexposure	Emergency First Aid Applicable for dusts or mists
Inhalation	Dust from grinding can cause irritation of the nose and throat. It also has the potential for causing transient or permanent respiratory disease, including occupational asthma and interstitial fibrosis, in a small percentage of exposed individuals. It is reported that cobalt dust is the most probable cause of such respiratory diseases. Symptoms include productive cough, wheezing, and shortness of breath, chest tightness and weight loss. Interstitial fibrosis (lung scarring) can lead to permanent disability or death. Certain pulmonary conditions may be aggravated by exposure.	If symptoms of pulmonary involvement develop (coughing, wheezing, shortness of breath, etc.) remove from exposure and seek medical attention.
Skin Contact	Can cause irritation or an allergic skin rash due to cobalt sensitization. Certain skin conditions, such as dry skin, may be aggravated by exposure.	If irritation or rash occurs, thoroughly wash affected area with soap and water and isolate from exposure. If irritation or rash persists, seek medical attention.
Eye Contact	Can cause irritation.	If irritation occurs, flush with copious amounts of water. If irritation persists, seek medical attention.
Ingestion	Reports outside the industry suggest that ingestion of significant amounts of cobalt has the potential for causing blood, heart and other organ problems.	If substantial quantities are swallowed, dilute with a large amount of water, induce vomiting and seek medical attention.

California Proposition 65 Compliance – WARNING: This product contains a chemical known to the state of California to cause cancer.

Section V – Fire and Explosion Hazard Data

Flash Point: N/A **Test Method Used:** -- -- **Flammable Limits:** N/A **LEL:** -- -- **UEL:** -- --
Hard Cemented Carbide Product is not a fire hazard. Dusts generated in grinding operations may ignite if allowed to accumulate and subjected to an ignition source.
Extinguishing Media: For powder fires smother with dry sand, dry dolomite, ABC type fire extinguisher, or flood with water.
Special Fire Fighting Procedures: For a powder fire confined to a small area, use a respirator approved for toxic dusts and fumes. For a large fire, fire fighters should use self-contained breathing apparatus.
Unusual Fire and Explosion Hazards: Dusts may present a fire or explosion hazard under rare favoring conditions of particle size, dispersion and strong ignition source. However, this is not expected to be a problem under normal handling conditions.

NFPA 704 SYSTEM OF IDENTIFICATION

The following information is provided to you in order to enable a fire fighter to determine what he must do in order to protect himself from injury while fighting a fire in an area containing the products described in this MSDS. It is not intended to provide full protective information for normal users of these products. Such protective information is more fully set out elsewhere in this MSGS and should be read carefully.

Health Hazard ----- rating 3
Flammability Hazard ----- rating 0
Reactivity Hazard ----- rating 0

Section VI – Reactivity Data

Stability: Unstable: _____
Stable: X

Conditions to Avoid: N/A

Incompatibility: Contact of dust with strong oxidizers cause fire or explosion.

Materials to Avoid: Strong Acids

Hazardous Decomposition Products:

None

Hazardous Polymerization: May Occur: _____
Will Not Occur: X

Conditions to Avoid: N/A

Section VII – Spill or Leak Procedures

Steps to be taken in Case Material is released or spilled: Ventilate area of spill. Clean up, using methods to avoid dust generation, such as vacuum (with appropriate filter to prevent airborne dust levels which exceed the PEL or TLV), wet dust mop or wet clean up. If airborne dust is generated, use an appropriate NIOSH approved respirator.

Waste Disposal Method: Dispose of in accordance with appropriate government regulations. May be sold as scrap for reclaim.

Section VIII – Special Protection Information

Respiratory Protection: Use an appropriate NIOSH approved respirator if airborne dust concentration exceeds the appropriate PEL or TLV. All appropriate requirements set forth in 29 CFR 1910.134 should be met.

Ventilation: Use local exhaust ventilation that is adequate to limit personal exposure to airborne dust to levels that do not exceed the PEL or TLV. If such equipment is not available, use respirators as specified above.

Protective Gloves: Protective Gloves or Barrier cream are recommended when contact with dust or mist is likely. Prior to applying the Barrier cream or use of protective gloves, wash thoroughly.

Eye Protection: Safety glasses with side shields or goggles should be worn.

Other Protective Equipment: Make sure tool is properly seated and safely clamped or held in place according to approved procedures. Always use machine guards and wear safety glasses and protective clothing to prevent injury in the event of tool breakage.

Section IX – Special Precautions

Precautions to be Taken in Handling and Storage: Maintain good housekeeping procedures to prevent dust accumulation during grinding. Avoid dust inhalation and direct skin contact with dust.

Do not strike or impact product with hardened steel hammer or similar device because of possible fracture/shattering of product. Product should be pressed if inserted into another metal part or product.

Other Precautions: Clean up, using methods to avoid dust generation such as vacuum (with appropriate filter to prevent airborne dust levels which exceed the PEL or TLV), wet dust mop or wet clean up. If airborne dust is generated, use an appropriate NIOSH approved respirator.

Wash hands thoroughly after handling and before eating or smoking. Wash exposed skin at the end of the work shift. Do not shake clothing, rags or other items to remove dust. Dust should be removed by washing or vacuuming (with appropriate filters) the clothing, rags, or other items.

Periodic medical examinations are recommended for individuals regularly exposed to dust or mist.

In case of questions please call:

SGS Tool Company
Environmental, Health & Safety
(330) 686-4141

ISSUE DATE: 04/28/09
SUPERSEDES: 10/01/04

Although SGS Tool Company has attempted to provide current and accurate information herein, SGS Tool Company makes no representations regarding the accuracy or completeness of the information and assumes no liability for any loss, damage, injury of any kind which may result from or arise out of the use of or reliance on the information by any person.

It shall be the responsibility of the customer purchasing this product to ensure that all employees/users of this product are familiar with and trained in the handling, use and hazards associated with this product as contained herein. This responsibility shall also extend directly to the user.